


## [2016.07.13]Download Cisco 400-101 Braindump VCE from Braindump2go[NQ1070-NQ1080]

2016.07.13 - Cisco Official News:400-101 CCIE Routing and Switching Written Exam 1119Q&As New Updated Today!Instant Free Download 400-101 PDF & 400-101 VCE from [Braindump2go.com](#)!100% Exam Pass Guaranteed! NEW QUESTION 1070 - NEW QUESTION 1080:1.|Braindump2go 2016.07.13 Cisco 400-101 CCIE Exam PDF and VCE 1119Q&As Dumps Download: <http://www.braindump2go.com/400-101.html> [100% Exam Pass Guaranteed! 2.|Braindump2go 2016.07.13 Cisco 400-101 CCIE Exam Questions PDF Download: <https://drive.google.com/folderview?id=0B272WrTALRHcQ1VmTHBkOEFvV00&usp=sharing> QUESTION 1070A network engineer is extending a LAN segment between two geographically separated data centers. Which enhancement to a spanning-tree design prevents unnecessary traffic from crossing the extended LAN segment? A. Modify the spanning-tree priorities to dictate the traffic flow.B. Create a Layer 3 transit VLAN to segment the traffic between the sites.C. Use VTP pruning on the trunk interfaces.D. Configure manual trunk pruning between the two locations. Answer: C QUESTION 1071The OSPF database of a router shows LSA types 1, 2, 3 and 7 only. Which type of area is this router connected to? A. backbone areaB. totally stubby areaC. stub areaD. not-so-stubby area Answer: D QUESTION 1072Which feature can you implement to most effectively protect customer traffic in a rate-limited WAN Ethernet service? A. HCBWFQB. IntServ with RSVPC. DiffServD. The IPsec VTI qos pre-classify commandE. Q-in-Q Answer: A QUESTION 1073An engineer has configured a router to use EUI-64, and was asked to document the IPv6 address of the router. The router has the following interface parameters:mac address C601:420F:0007subnet 2001:DB8:0:1::/64 A. 2001:DB8:0:1:C601:42FF:FE0F:7B. 2001:DB8:0:1:FFFF:C601:420F:7C. 2001:DB8:0:1:FE80:C601:420F:7D. 2001:DB8:0:1:C601:42FE:800F:7 Answer: A QUESTION 1074Which command configures port security on a switch to enable permanent MAC address learning on the interface? A. switchport port-security mac-address-learning enableB. switchport port-security mac-address timer 0C. switchport port-security mac-address stickyD. switchport port-security mac-address maximum 1 stickyE. switchport port-security mac-address permanent Answer: C QUESTION 1075If EIGRP and OSPF are configured within an administrative domain for the same network, which value can you change so that the OSPF becomes the installed routing protocol for all routes? A. Local preferenceB. MetricC. MEDD. Administrative distanceE. Prefix length Answer: E QUESTION 1076Which three components are in an MPLS header? (choose three) A. a 4-bit experimental use fieldB. a 4-bit label stack entryC. an 8-bit TTL D. a 2-bottom of stackE. a 3-bit experimental use fieldF. a 20-bit label Answer: CEF QUESTION 1077What is the main function of VRF-lite? A. To allow devices to use labels to make Layer 2 Path decisionsB. To segregate multiple routing tables on a single deviceC. To connect different autonomous systems together to share routesD. To route IPv6 traffic across an IPv4 backbone Answer: B QUESTION 1078Refer to the exhibit. Which prefixes will have their distance changed?



```
router eigrp 100
 network 10.0.0.0
access-list 10 permit 10.1.0.0
```

A. all prefixes matching access-list 10 learned from peers in the range 10.1.12.0- 10.1.12.255B. all internal prefixes in the range 10.1.12.0-10.1.12.255 learned from peers matching access-list 10C. all internal prefixes matching access-list 10 learned from peers in the range 10.1.12.0- 10.1.12.255D. all prefixes in the range 10.1.12.0-10.1.12.255 learned from peers matching access-list Answer: C QUESTION 1079Which two methods do IPsec VTIs used to identify and transmit encrypted traffic through the tunnel? (choose two) A. static routingB. dynamic routingC. object groupsD. ACLsE. NAT Answer: AB QUESTION 1080When you deploy DMVPN, what is the purpose of the command crypto isakmp key ciscotest address 0.0.0.0 0.0.0.0 ? A. It is configured on hub and spoke router to establish peeringB. It is configured on hub to set the pre-shared key for the spoke routersC. It is configured on the spokes to indicate the hub routerD. It is configured on the Internet PE routers to allow traffic to traverse the ISP core Answer: B !!!RECOMMEND!!! 2016.07.13 Braindump2go Latest Cisco 400-101 Exam PDF and VCE 1119Q&As Instant Download: <http://www.braindump2go.com/400-101.html> [100% Real Questions Guaranteed!] Cisco 400-101 Exam Questions PDF - Google Drive: <https://drive.google.com/folderview?id=0BwwEERkugSaLbUR5WjhsemNKY00&usp=sharing> <https://drive.google.com/folderview?id=0B75b5xYLjSSNdmdKVDE2WUw4VGM&usp=sharing>