[2016-August-New100% Real Exam Questions-Cisco 300-209 Dumps VCE PDF Dumps 237Q&As Download[NQ81-NQ90

!!!August 2016 Cisco Official News!!!CCNP Security 300-209 SIMOS: Implementing Cisco Secure Mobility Solutions (SIMOS) Exam Questions Updated Today! Instant Free Download 300-209 SIMOS PDF & 300-209 SIMOS VCE Dumps from Braindump2go.com!100% Pass Guaranteed!100% Real Exam Questions! NEW QUESTION 81 - NEW QUESTION 90: 1.|2016/08 Latest 300-209 SIMOS PDF & 300-209 SIMOS VCE 237Q&As: http://www.braindump2go.com/300-209.html2.|2016/08 Latest 300-209 SIMOS SISAS Exam Questions PDF:

https://drive.google.com/folderview?id=0B272WrTALRHcRmVtQ29JNWk3Nzg&usp=sharing QUESTION 81When you are configuring a DMVPN network, which tunnel mode should you use for the hub router configuration? A. GRE multipointB. provides secure, on-demand meshed connectivity? A. Easy VPNB. IPsec VPNC. mGRED. DMVPN Answer: D QUESTION 83Which of these is true regarding tunnel configuration when deploying a Cisco ISR as a DMVPN hub router? A. Only one tunnel can be created per tunnel source interface.B. Only one tunnel can be created and should be associated with a loopback interface for dynamic redundancyC. The GRE tunnel key is used to encrypt the traffic going through the tunnel through the hub.D. run multiple parallel DMVPNs on the hub router, but each tunnel requires a unique tunnel key. Answer: D QUESTION 84When you are configuring a hub-and-spoke DMVPN network, which tunnel mode should you use for the spoke router configuration? A. GRE multipointB. Classis point-to-point GREC. IPsec multipointD. Nonbroadcast multiaccess Answer: A QUESTION 85With Cisco ASA active/standby failover, by default, how many monitored interface failures will cause failover to occur? A. 1B. 2C. 3D. 4E. 5 Answer: A QUESTION 86Which two statements about the running configuration of the Cisco ASA are true? (Choose Two) A. The auto NAT configuration causes all traffic arriving on the inside interface destined to any outside destinations to be translated with dynamic port address transmission using the outside interface IP address.B. The Cisco ASA is using the Cisco ASDM image from disk1:/asdm-642.binC. The Cisco ASA is setup as the DHCP server for hosts that are on the inside and outside interfaces.D. SSH and Cisco ASDM access to the Cisco ASA requires AAA authentication using the LOCAL user database.E. The Cisco ASA is using a persistent self-signed certified so users can authenticate the Cisco ASA when accessing it via ASDM Answer: AE OUESTION 87Which option lists the main tasks in the correct order to configure a new Layer 3 and 4 inspection policy on the Cisco ASA appliance using the Cisco ASDM Configuration > Firewall > Service Policy Rules pane? A. 1. Create a class map to identify which traffic to match. 2. Create a policy map and apply action(s) to the traffic class(es). 3. Apply the policy map to an interface or globally using a service policy.B. 1. Create a service policy rule.2. Identify which traffic to match.3. Apply action(s) to the traffic.C. 1. Create a Layer 3 and 4 type inspect policy map.2. Create class map(s) within the policy map to identify which traffic to match.3. Apply the policy map to an interface or globally using a service policy.D. 1. Identify which traffic to match.2. Apply action(s) to the traffic.3. Create a policy map.4. Apply the policy map to an interface or globally using a service policy. Answer: B QUESTION 88By default, how does a Cisco ASA appliance process IP fragments? A. Each fragment passes through the Cisco ASA appliance without any inspections.B. Each fragment is blocked by the Cisco ASA appliance.C. The Cisco ASA appliance verifies each fragment and performs virtual IP re-assembly before the full IP packet is forwarded out.D. The Cisco ASA appliance forwards the packet out as soon as all of the fragments of the packet have been received. Answer: C QUESTION 89Which other match command is used with the match flow ip destination-address command within the class map configurations of the Cisco ASA MPF? A. match tunnel-groupB. match access-listC. match default-inspection-trafficD. match portE. match dscp Answer: A QUESTION 90Which Cisco ASA configuration is used to configure the TCP intercept feature? A. a TCP mapB. an access listC. the established commandD. the set connection command with the embryonic-conn-max optionE. a type inspect policy map Answer: D !!!RECOMMEND!!! Braindump2go 2016/08 New Cisco 300-209 SIMOS Exam VCE and PDF 237Q&As Dumps Download:http://www.braindump2go.com/300-209.html [100% 300-209 Exam Pass Promised!] 2016/08 Cisco 300-209 SIMOS New Questions and Answers PDF: https://drive.google.com/folderview?id=0B272WrTALRHcRmVtQ29JNWk3Nzg&usp=sharing