## [2016-July-LatestCisco 300-206 VCE Exam Questions 223q Instant Download in Braindump2go[NQ51-NQ60

2016/07 Cisco Official News300-206:Implementing Cisco Edge Network Security Solutions Exam Questions Updated Today! Instant Free Download 300-206 PDF & 300-206 VCE Dumps from Braindump2go.com!100% Pass Guaranteed! 100% Real Exam Ouestions! NEW OUESTION 51 - NEW OUESTION 60: 1.|2016/07 Latest Cisco 300-206 PDF & 300-206 VCE 223Q&As:http://www.braindump2go.com/300-206.html2.|2016/07 Latest Cisco 300-206 Exam Questions PDF:https://drive.google.com/folderview?id=0B272WrTALRHcSzRwRV9LM1pOcWs&usp=sharing QUESTION 51Which three configurations are needed to enable SNMPv3 support on the Cisco ASA? (Choose three.) A. SNMPv3 Local EngineIDB. SNMPv3 Remote EngineIDC. SNMP UsersD. SNMP GroupsE. SNMP Community StringsF. SNMP Hosts Answer: CDF QUESTION 52Which two configurations are the minimum needed to enable EIGRP on the Cisco ASA appliance? (Choose two.) A. Enable the EIGRP routing process and specify the AS number.B. Define the EIGRP default-metric.C. Configure the EIGRP router ID.D. Use the neighbor command(s) to specify the EIGRP neighbors.E. Use the network command(s) to enable EIGRP on the Cisco ASA interface(s). Answer: AE QUESTION 53All 30 users on a single floor of a building are complaining about network slowness. After investigating the access switch, the network administrator notices that the MAC address table is full (10,000 entries) and all traffic is being flooded out of every port. Which action can the administrator take to prevent this from occurring? A. Configure port-security to limit the number of mac-addresses allowed on each portB. Upgrade the switch to one that can handle 20,000 entriesC. Configure private-vlans to prevent hosts from communicating with one anotherD. Enable storm-control to limit the traffic rateE. Configure a VACL to block all IP traffic except traffic to and from that subnet Answer: A QUESTION 54A network printer has a DHCP server service that cannot be disabled. How can a layer 2 switch be configured to prevent the printer from causing network issues? A. Remove the ip helper-addressB. Configure a Port-ACL to block outbound TCP port 68C. Configure DHCP snoopingD. Configure port-security Answer: C QUESTION 55A switch is being configured at a new location that uses statically assigned IP addresses. Which will ensure that ARP inspection works as expected? A. Configure the 'no-dhcp' keyword at the end of the ip arp inspection commandB. Enable static arp inspection using the command 'ip arp inspection static vlan vlan- numberC. Configure an arp access-list and apply it to the ip arp inspection commandD. Enable port security Answer: C QUESTION 56Which two voice protocols can the Cisco ASA inspect? (Choose two.) A. MGCPB. IAXC. SkypeD. CTIOBE Answer: AD OUESTION 57You have explicitly added the line deny ipv6 any log to the end of an IPv6 ACL on a router interface. Which two ICMPv6 packet types must you explicitly allow to enable traffic to traverse the interface? (Choose two.) A. router solicitationB. router advertisementC. neighbor solicitationD. neighbor advertisementE. redirect Answer: CD QUESTION 58Enabling what security mechanism can prevent an attacker from gaining network topology information from CDP? A. MACsecB. Flex VPNC. Control Plane ProtectionD. Dynamic Arp Inspection Answer: A QUESTION 59Which log level provides the most detail on the Cisco Web Security Appliance? A. DebugB. CriticalC. TraceD. Informational Answer: C QUESTION 60What is the lowest combination of ASA model and license providing 1 Gigabit Ethernet interfaces? A. ASA 5505 with failover license optionB. ASA 5510 Security+ license optionC. ASA 5520 with any license optionD. ASA 5540 with AnyConnect Essentials License option Answer: B !!!RECOMMEND!!! Braindump2go 2016/07 New Cisco 300-206 Exam VCE and PDF 223Q&As Dumps Download:http://www.braindump2go.com/300-206.html [100% 300-206 Exam Pass Promised!] 2016/07 Cisco 300-206 New Questions and Answers PDF:

https://drive.google.com/folderview?id=0B272WrTALRHcSzRwRV9LM1pOcWs&usp=sharing