

2017-Aug.-UpdatedValid Braindump2go 300-170 Brain Dumps PDF 75Q Offer[41-50]

2017 August New 300-170 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 300-170 Questions:
1.|2017 New 300-170 Exam Dumps (PDF & VCE) 75Q&As Download:<https://www.braindump2go.com/300-170.html> 2.|2017 New 300-170 Exam Questions & Answers Download:
<https://drive.google.com/drive/folders/0B75b5xYLjSSNUlhkLWQ5UVdfaWM?usp=sharing> QUESTION 41You are trouble shooting node discovery issues by using the aci diag fmv read command.Which description of the node status when the CLI output shows a status of Discovering is true? A. The node is decommissionedB. The node ID is configured, but not discovered yetC. The node is discovered, but an IP address is not assigned yetD. The node is discovered, but the node ID policy is not configured yet Answer: B QUESTION 42Which two options are purposes of a device package? (Choose two) A. to identify a set of network or service functions required by the applicationB. to provide a leaf and spine devices with operating systems and firmwareC. to provide a Cisco APIC with information about device specificsD. to render the services required by a graphE. to manage a class of service devices Answer: CE QUESTION 43You have a network that has three subnets. You migrate the network to a Cisco ACI fabric.You want to bridge the three subnets without changing the IP addresses of the endpoints.The default gateway for the endpoints does not sit on the ACI fabric.Which action must you take to keep the three subnets in a single Hood domain? A. Create multiple bridge domains that have unicast routing disabled within the same EPO Connect the existing subnets to the bridge domains B. Create one bridge domain that has unicast routing disabled and connect the existing subnets to the bridge domainC. Create one bridge domain that has unicast routing enabled and create corresponding subnets inside the bridge domain Connect the existing network to the bridge domainD. Create multiple bridge domains that have unicast routing enabled within the saw EPG Create corresponding subnets inside the bridge domains and connect the existing network to the bridge domains. Answer: C QUESTION 44 Which statement accurately describes Cisco ACI flooding mode for unknown unicast traffic? A. By default unknown unicast traffic floods the bridge domainB. By default, all unknown unicast traffic is droppedC. A hardware proxy must be used for flooding modeD. By default, an unknown unicast traffic is sent to the spine proxy Answer: D QUESTION 45Refer to the exhibit. You are verifying connectivity within a leaf device.You attempt to connect to a destination server in VLAN 17, and you then run the show mac address-table command as shown.Why does the show mac address-table output show a different VLAN?



Legend	Primary	Secondary	Gateway
* 14	0045.0034.1016		dynamic
* 18	0045.0034.1016		dynamic

A. The wrong AEP is attached to the leaf portsB. The VLAN configuration on the leaf switch is incorrectC. The VLAN ID shown is used for identification and internal mapping within the ACI leafD. When traffic appears, the Cisco ACI marks ports with VLAN 17 Answer: A QUESTION 46You deploy AVS for Virtual Manager integration and you add a host that has five VMNICs. You must use VXLAN to maximize the load balancing of the traffic inside the fabric.How many VMKNICs must you add? A. 2B. 3C. 4D. 8 Answer: C QUESTION 47Refer to the exhibit. You define the port profiles as shown in the exhibit, and then you assign the P10GIG port profile to interface el. Which option is the result of this configuration? A. The speed of the interface is 10 GbpsB. The speed of the interface is 1 GbpsC. The interface uses the maximum speed available for the physical interface.D. The speed of the interface is 100 Gbps Answer: C QUESTION 48What occurs when you make an interface a member of an existing VRF in Cisco NX-OS? A. The a VRF-Aware services start to be filteredB. You are prompted to enter an IP address assignment C. All of the Layer 3 configurations are removedD. The state of the interface is changed to down Answer: CExplanation: <https://supportforums.cisco.com/document/133711/vrf-configuration-and-verification-nexus-7000> QUESTION 49A unicast packet enters into the front panel port of a leaf switch.The leaf switch performs a forwarding lookup for the packet destination IP address and has a miss result Assuming default configuration, which statement about what happens next is true? A. The packet is sent to the forwarding proxy in the spine switchB. The packet is dropped on the leaf switchC. The packet is sent to another leaf switch within the same bridge domainD. The packet is flooded across the entire fabric because it is an unknown unicast. Answer: D QUESTION 50Which statement about POAP licensing correctly describes temporary licensing? A. Temporary licensing is invoked by using the license grace-period commandB. Temporary licensing is enabled automatically and is valid for 60 daysC. Temporary licensing is invoked by using the license Install commandD. Temporary licensing is enabled automatically and is valid for 30 days Answer: D !!!RECOMMEND!!! 1.|2017 New 300-170 Exam Dumps (PDF & VCE) 75Q&As Download: <https://www.braindump2go.com/300-170.html> 2.|2017 New 300-170 Study Guide Video: YouTube Video: [YouTube.com/watch?v=RMJG-FygmI4](https://www.youtube.com/watch?v=RMJG-FygmI4)