

[2017-Nov.-NEW Offering New 400-101 Exam PDF and 400-101 Exam VCE Dumps for Free Downloading[106-116

2017 November New Cisco 400-101 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 400-101 Questions:
 1. 2017 New 400-101 Exam Dumps (PDF & VCE) 748Q&As Download: <https://www.braindump2go.com/400-101.html>
 2. 2017 New 400-101 Exam Questions & Answers Download: <https://drive.google.com/drive/folders/0B75b5xYLjSSNWWsyOTJ2UHJFVVU?usp=sharing>
 QUESTION 106 Refer to the exhibit.
 With BGP always-compare-med enabled, which BGP entry is installed in the RIB?

```
entry1: AS(PATH) 400, med 150, external, rid 2
entry2: AS(PATH) 100, med 100, external, rid 1
entry3: AS(PATH) 400, med 100, internal, rid 3
```

- A. Entry 1 because it was installed first (oldest) in the BGP table.
 B. Entry 1 because it has the best MED of the external routes.
 C. Entry 2 because it has the lowest router ID.
 D. Entry 3 because it has the lowest MED.
 Answer: D
 QUESTION 107 Refer to the exhibit. What type of IS-IS is configured on R1?

```
R1
interface Loopback0
 ip address 172.16.1.1 255.255.255.255
 ip router isis
 ipv6 address 2001:DB8:1111::1/128
 ipv6 router isis

interface Loopback1
 ip address 192.168.10.1 255.255.255.0
 ip router isis
 ipv6 address 2001:DB8:10::1/48
 ipv6 router isis

router isis
 net 01.0001.0000.0000.0001.00
```

- A. VRF-aware IS-IS.
 B. IS-IS version 2.
 C. single-topology IS-IS.
 D. multi-process IS-IS.
 Answer: C
 QUESTION 108 Which statement about Cisco StackWise technology is true?
 A. All switches in a stack share configuration and routing information to behave as a single unit.
 B. Removing switches can affect stack performance.
 C. Only the master switch acts as a forwarding processor.
 D. Every switch in a stack has its own independent and uncoordinated configuration file, which enables it to become the stack master if the previous master fails.
 Answer: A
 Explanation: Configuration and routing information is shared by every switch in the stack, creating a single switching unit.

http://www.cisco.com/c/en/us/products/collateral/switches/catalyst-3750-series-switches/prod_white_paper09186a00801b096a.html

QUESTION 109 Refer to the exhibit. Which two statements are true regarding prefix 10.1.0.0/24? (Choose two.)

```
MC#sh pfr master traffic-class
OER Prefix Statistics:
Pas - Passive, Act - Active, S - S
P - Percentage below threshold, J
MOS - Mean Opinion Score
Los - Packet Loss (packets-per-mil
E - Egress, I - Ingress, Bw - Band
U - unknown, * - uncontrolled, +
# - Prefix monitor mode is Special
% 10.1.0.0/24: op. Prefix n

DstPrefix      Appl_ID Desc Pr
State
PasLDly PasLDly PasSun
ActSDly ActLDly ActSun
-----
10.1.0.0/24          N N
INPOLICY*
52 52 0
51 51 0
```

- A. The prefix is in policy, and Cisco PfR rerouted the traffic via 10.4.5.3 Et0/1 because of an OOP event.
 B. Cisco PfR is monitoring the prefix via passive NetFlow mode only.
 C. Cisco PfR is monitoring the prefix via active, fast, or active throughput IP SLA probe mode only.
 D. The prefix is in policy, and Cisco PfR did not reroute the traffic via 10.4.5.3 Et0/1 because the traffic was previously in policy.
 E. Cisco PfR is monitoring the prefix via mode monitor, which provides both NetFlow and IP SLA measurements.
 Answer: DE
 QUESTION 110 Which feature can mitigate hung management sessions?
 A. Control Plane Policing
 B. the service tcp-keepalives-in and service tcp-keepalives-out command
 C. the service tcp-small servers command
 D. vty line

ACLs Answer: B QUESTION 111 What are two requirements for BFD static route support? (Choose two) A. CEF must be configured on all routers that will carry traffic. B. BFD must be configured on all Ethernet, virtual-template, and dialer interfaces that will carry traffic. C. All routers that will carry traffic must have the same software version. D. All routers that will carry traffic must be the same model. E. Parameters must be configured on all routers that will carry traffic. F. Parameters must be configured on all interfaces that will carry traffic. Answer: A F QUESTION 112 Refer to the exhibit. Which two actions can you take to allow the network 172.29.224.0/24 to be reachable from peer 192.168.250.53? (Choose two)

```
R1
ip community-list 10 permit 64512:100 64512:200 64512:416
route-map INTERNET-OUT permit 10
 match community 10

router bgp 64512
 no synchronization
 neighbor INTERNET peer-group
 neighbor INTERNET remote-as 64513
 neighbor INTERNET password cisco
 neighbor 192.168.250.53 peer-group INTERNET

address-family ipv4
 neighbor INTERNET send-community both
 neighbor INTERNET route-map INTERNET-OUT out

R1#show bgp 172.29.224.0

BGP routing table entry for 172.29.224.0/24, version 60725
Paths: (1 available, best #1, table default)
Multipath: eBGP iBGP
  Advertised to update-groups:
    3          4          7
  53739
    10.10.153.12 from 10.10.153.120 (10.10.153.12)
      Origin IGP, metric 0, localpref 130, valid, ex
      Community: 64512:555 64513:200 64513:53090
```

A. Modify the community list to match communities 64513:69040 attached to 172.29.224.0/24. B. Configure soft reconfiguration to peering 192.168.250.53. C. Modify the outbound route map to permit all additional routes. D. Configure additional address families to peering 192.168.250.53. E. Modify the inbound route map to permit all additional routes. F. Modify the community list to match community 64513:64090 attached to 172.29.224.0/24. Answer: C F QUESTION 113 Which two options are potential impacts of microbursts? (Choose two.) A. unnecessary broadcast traffic B. asymmetric routing C. tail drops D. invalid checksum errors E. packet loss F. unicast flooding Answer: C E QUESTION 114 Refer to the exhibit. Which two conclusions can you draw from this command and its output? (Choose two.)

```
R10#ping mpls ipv4 192.168.40.171/32
www.braindump2go.com
00000
Success rate is 0 percent (0/5)
```

A. R10 has a missing label binding for 192.168.40.171/32. B. The MPLS ping failed. C. 192.168.40.171/32 exists in the global routing table. D. A valid LSP exists, and it matches the corresponding MPLS FEC. E. The MPLS ping was successful. F. R10 has valid label binding for 192.168.40.171/32 Answer: A B QUESTION 115 Which DHCP message type does the DHCP server send to a client to confirm its allocated IP address? A. DHCPACK B. DHCP OFFER C. DHCP DISCOVER D. DHCP REQUEST Answer: A QUESTION 116 Which statement about a Cisco APIC controller versus a more traditional SDN controller is true? A. APIC uses a policy agent to translate policies into instructions. B. APIC supports OpFlex as a Northbound protocol. C. APIC does support a Southbound REST API. D. APIC uses an imperative model Answer: A !!! RECOMMEND !!! 1. | 2017 New 400-101 Exam Dumps (PDF & VCE) 748 Q&As Download: <https://www.braindump2go.com/400-101.html> 2. | 2017 New 400-101 Study Guide Video: YouTube Video: [YouTube.com/watch?v=xcUjk7uBioM](https://www.youtube.com/watch?v=xcUjk7uBioM)