Cisco 642-997 Practice Tests From People Who Created Cisco 642-997 Exam

CISCO NEWS: 642-997 Exam Questions has been Updated Today! Get Latest 642-997 VCE and 642-997 PDF Instantly! Welcome to Download the Newest Braindump2go 642-997 VCE&642-997 PDF Dumps:

http://www.braindump2go.com/642-997.html (137 Q&As)] Exam Code: 642-997Exam Name: Implementing Cisco Data Center Unified Fabric (DCUFI)Certification Provider: Cisco642-997 Dump,642-997 PDF,642-997 VCE,642-997 DUCFI Book,642-997 DUCFI PDF,642-997 Study Guide,642-997 Training Material,642-997 Braindump,642-997 eBook,642-997 DUCFI Book,642-997 Practice Exam,642-997 Practice Test,642-997 Practice Questions Implementing Cisco Data Center Unified Fabric (DCUFI): 642-

CHECK OUT

997 Product Description Exam Number/Code: 642-997 Exam Number/Code: 642-997 "Implementing Cisco Data Center Unified Fabric (DCUFI)", also known as 642-997 exam, is a Cisco Certification. With the complete collection of questions and answers, Braindump2go has assembled to take you through 137 Q&As to your 642-997 Exam preparation. In the 642-997 exam resources, you will cover every field and category in Cisco CCNP Data Center helping to ready you for your successful Cisco Certification. Questions and Answers: 137 Q&As Free Demo Download Updated: Dec 4, 2015 Braindump2go offers free demo for 642-997 exam (Implementing Cisco Data Center Unified \$120.00 \$99.99 Fabric (DCUFI)). You can check out the interface, question quality and usability of our practice

✓ Printable PDF
✓ Premium VCE + VCE Simulator

QUESTION 101If you are using NAT in your data center, which load balancing would you be likely to use within your GLBP configuration? A. noneB. round-robinC. host dependentD. weighted Answer: C QUESTION 102Which command specifies a load-balancing method based on the MAC address of a host where the same forwarder is always used for a particular host while the number of GLBP group members remains unchanged? A. load-balancing host-dependentB. load-balancing mac-pinningC. load-balancing round-robinD. load-balancing weighted Answer: A QUESTION 103Which feature allows routing protocols to remain in the data path during a supervisor failover? A. Cisco Nonstop ForwardingB. Cisco Stateful SwitchoverC. Cisco Express ForwardingD. Cisco Route Processor Redundancy Answer: A QUESTION 104Which two functions are enabled when you set up vPC+ at the FabricPath edge? (Choose two.) A. the ability to attach Cisco Fabric Extenders in FEX active/active mode B. the ability to stop all Layer 3 egress trafficC. the ability to attach servers to edge switches with port-channel teamingD. ability to attach additional Classic Ethernet switches in vPC+ mode Answer: AC QUESTION 105How does addition of bandwidth between spine and leaf switches in a FabricPath architecture get utilized? A. Links between the same set of switches are automatically added to a port channel.B. Adding additional bandwidth is handled dynamically using the 802.1AX protocol.C. Traffic is load shared automatically across the available paths to the destination.D. FabricPath uses hardware bonding of physical interfaces to form higher-speed links. Answer: C QUESTION 106Which two advantages does FabricPath have over Spanning Tree in implementing a loop-free network topology design? (Choose two.) A. Blocked links can be brought in to service if active links fail.B. Convergence times are faster.C. Multipath forwarding is supported for unicast and multicast Layer 2 and Layer 3 traffic. D. Unknown unicast addresses are flooded in through the originating port. Answer: BC QUESTION 107Which four statements about reserved VLANs in Cisco NX-OS are true? (Choose four.) A. The range of reserved VLANs cannot be changed.B. The number of reserved VLANs is 96.C. A change to the range of reserved VLANs can be performed only in the VDC default.D. A write-erase procedure restores the default reserved VLAN range.E. The number of reserved VLANs is 128.F. A reload is needed for changes to take place.G. The configuration must be saved for changes to take place. Answer: CEFG QUESTION 108Which two RFCs are supported by Cisco NX-OS devices for OSPFv2? (Choose two.) A. RFC 2238B. RFC 1918C. RFC 1583D. RFC 2453E. RFC 2740 Answer: AC QUESTION 109Which action limits the maximum number of routes that are allowed in the routing table? A. Use a filter BGP.B. Use only static routes.C. Use the maximum routes command inside address family.D. Use a route map to filter routes. Answer: C QUESTION 110Which three options of encryption are supported in PIM hello messages? (Choose three.) A. cleartextB. DES-SHA1C. DES-CBC3-SHAD. Cisco Type 7E. RC4-SHAF. 3DES Answer: ADF QUESTION 111Which command is used to associate EID-to-RLOC for a LISP site? A. #feature lispB. #ipv6 lisp itrC. #ip lisp database-mappingD. #ip lisp itr map-resolver Answer: C QUESTION 112In OTV, how are the VLANs split when a site has two edge devices? A. They are configured manually by user.B. They are split in half among each edge device.C. They are

split as odd and even VLAN IDs on each edge device.D. It is not possible to have two edge devices in same site. Answer: C QUESTION 113Which statement about the MPLS feature set is true? A. It is not license dependent.B. It can be installed from any VDC.C. It can be enabled only in the default VDC.D. It must be installed from the default VDC. Answer: D FREE DOWNLOAD: NEW UPDATED 642-997 PDF Dumps & 642-997 VCE Dumps from Braindump2go:

 $http://www.braindump2go.com/642-997.html~(137~Q\&A)~ \\ \textbf{Implementing~Cisco~Data~Center~Unified~Fabric~(DCUFI):~642-997.html}$

