[Feb-2017-UpdatedExam Collection 644-906 Dumps and 644-906 New Questions - Braindump2go[Q1-Q10

2017 Feb. NEW 644-906: Implementing and Maintaining Cisco Technologies Using IOS XR - (IMTXR) Exam Questions Updated Today!Free Instant Download 644-906 Exam Dumps (PDF & VCE) 80Q&As from www.braindump2go.com Today! 100% Real Exam Questions! 100% Exam Pass Guaranteed! 1. NEW 644-906 Exam Dumps (PDF & VCE) 800&As Download: http://www.braindump2go.com/644-906.html 2.|EW 644-906 Exam Questions & Answers Download: https://ldrv.ms/f/s!AvI7wzKf6QBjgktwWG6fOotKPwTZ QUESTION 1Which of the following functions can be configured in the Administration Config mode? (Choose two) A. BGP routingB. MPLS Traffic EngineeringC. SDR hostnameD. Secure Shell loginE. nonowner SDR Answer: CE QUESTION 2Which two of the following statements regarding task-based authorization are true? (Choose two.) A. The user group concept in Cisco IOS XR Software relates to a group of users with common characteristics. B. All of the user groups are precreated by default.C. In addition to the predefined task groups, Cisco IOS XR Software provides the ability to custom create task groups consisting of individual tasks.D. User groups and task groups cannot inherit from other user groups and task groups. Answer: AC QUESTION 3A network administrator needs to configure a default IPv4 route for a Cisco CRS-1 router. Which Cisco IOS XR command will accomplish this task? A. RP/0/RSP0/CPU0:R15(config-static)#ip route 0.0.0.0 0.0.0.0 10.52.204.161B. RP/0/RSP0/CPU0:R15(config-static-afi)#0.0.0.0/0 10.52.204.161C. RP/0/RSP0/CPU0:R15(config)#router static 0.0.0.0/32 10.52.204.161D. RP/0/RSP0/CPU0:R15#ip default-network 0.0.0.0 10.52.204.161 255.255.255.255E. it is not possible to configure static routes in Cisco IOS XR Software Answer: B QUESTION 4 What is the main function of LPTS? A. filter routing updatesB. maintain the Internal Forwarding Information Base (IFIB)C. classify transit packetsD. guarantee reliable transport service for network management requests Answer: B QUESTION 5How would you configure IS-IS process TEST to support MPLS Traffic Engineering extensions on level 1 and 2 that are intending to run a tunnel across TenGigE 0/0/0/0? A. mpls ldp traffic-eng level-1-2mpls traffic-eng router-id 1.1.1.1router isis TESTinterface Ten 0/0/0/0address-family ipv4 unicastB. router isis TESTnet 49.0001.0001.0001.0001.00address-family ipv4 unicastmetric-style wide mpls traffic-eng router-id 1.1.1.1mpls traffic-eng level-1-2interface Ten 0/0/0/0address-family ipv4 unicastC. router isis TESTnet 49.0001.0001.0001.0001.0001.00address-family ipv4 unimetric-style wideinterface Ten 0/0/0/0address-family ipv4 unicastmpls traffic-eng router-id 1.1.1.1mpls traffic-eng level-1-2D. mpls ldprouter isis TESTinterface Ten 0/0/0/0address-family ipv4 unicast mpls traffic-eng level-1-2mpls traffic-eng router-id 1.1.1.1 Answer: B OUESTION 6When running MPLS Traffic Engineering with Cisco IOS XR Software, which three criteria can be seen when the show mpls traffic-eng tunnels command is executed on a midpoint router? (Choose three.) A. tunnel roleB. TE metricC. tunnel IDD. physical bandwidthE. incoming and outgoing label Answer: ACE QUESTION 7What are the two prerequisites for enabling multicast-only fast reroute (MoFRR) in a network? (Choose two.) A. There must be an Equal-Cost Multipath (ECMP) topology.B. IP multicast traffic must use the group address 232.0.0.0/8.C. PIM-SSM needs to be configured.D. There must be a valid reverse path back to the multicast source. Answer: AD QUESTION 8Which CLI command can be used to display interfaces statistics? A. RP/0/RSP1/CPU0:ASR9006#monitor interface B. RP/0/RSP1/CPU0:ASR9006#show interfaces summary C. RP/0/RSP1/CPU0:ASR9006#show interfaces statistics | inc errors D. RP/0/RSP1/CPU0:ASR9006#show interfaces accounting | inc errorsE. RP/0/RSP1/CPU0:ASR9006(admin)#show flow platform producer statistics location 0/0/CPU0F. RP/0/RSP1/CPU0:ASR9006(admin)##show interfaces statistics Answer: A QUESTION 9Which three types of packet drop statistics can be determined by using the following Cisco IOS XR CLI show command? (Choose three.)RP/0/RSP1/CPU0:ASR9006-A#show cef ipv4 drops location all A. no route dropsB. no adjacency dropsC. RPF dropsD. ACL dropsE. asymmetric routing dropsF. Cisco Express Forwarding exception drops Answer: ABC QUESTION 10Referring to the configuration output exhibit, which set of commands below will allow you to insert a new line just before the permit any statement? A. :router#configure:router(config)#ipv4 access-list Ethernet_In:router(config-ipv4-acl)# 2.5 deny udp any eq tftp any B. :router#configure:router(config)#ipv4 access-list Ethernet_In:router(config-ipv4-acl)# insert after 2 deny udp any eq tftp any C. :router #resequence access-list ipv4 Ethernet In:router#configure:router(config)#ipv4 access-list Ethernet_In:router(config-ipv4-acl)#25 deny udp any eq tftp anyD. :router#configure:router(config)#ipv4 access-list Ethernet_In :router(config-ipv4-acl)#move 3 to 4:router(config-ipv4-acl)#3 deny udp any eq tftp any Answer: C !!!RECOMMEND!!! 1.|NEW 644-906 Exam Dumps (PDF & VCE) 80Q&As Download:http://www.braindump2go.com/644-906.html 2.|EW 644-906 Study Guide Video: YouTube Video: YouTube.com/watch?v=7U0WVbIpck0