

## [Jan-2018-Updated!Braindump2go 300-208 PDF and VCE Instant Download[Q107-Q117]

2018 January new Cisco 300-208 Exam Dumps with PDF and VCE Free Updated Today! Following are some new added 300-208

Exam Questions:1.|2018 New 300-208 Exam Dumps (PDF 7 VCE) 320Q&As Download:

<https://www.braindump2go.com/300-208.html>2.|2018 New 300-208 Exam Questions & Answers Download:

<https://drive.google.com/drive/folders/0B75b5xYLjSSNdm14RFVqa0Q1YUU?usp=sharing>  
QUESTION 107 Which two Cisco ISE administration options are available in the Default Posture Status setting? (Choose two.)  
A. Unknown  
B. Compliant  
C. FailOpen  
D. FailClose  
E. Noncompliant  
Answer: BE  
QUESTION 108 Which two portals can be configured to use portal FQDN? (Choose two.)  
A. admin  
B. sponsor  
C. guest  
D. my devices  
E. monitoring and troubleshooting  
Answer: BD  
QUESTION 109 Which five portals are provided by PSN? (Choose five.)  
A. guest  
B. sponsor  
C. my devices  
D. blacklist  
E. client provisioning  
F. admin  
G. monitoring and troubleshooting  
Answer: ABCDE  
QUESTION 110 When you add a new PSN for guest access services, which two options must be enabled under deployment settings? (Choose two.)  
A. Admin  
B. Monitoring  
C. Policy Service  
D. Session Services  
E. Profiling  
Answer: CD  
QUESTION 111 In Cisco ISE, which probe must be enabled to collect profiling data using Device Sensor?  
A. RADIUS  
B. SNMPQuery  
C. SNMPTrap  
D. Network Scan  
E. Syslog  
Answer: A  
QUESTION 112 Which two profile attributes can be collected by a Cisco Catalyst Switch that supports Device Sensor? (Choose two.)  
A. LLDP agent information  
B. user agent  
C. DHCP options  
D. open ports  
E. operating system  
F. trunk ports  
Answer: AC  
QUESTION 113 Which two profile attributes can be collected by a Cisco Wireless LAN Controller that supports Device Sensor? (Choose two.)  
A. LLDP agent information  
B. user agent  
C. DHCP options  
D. open ports  
E. CDP agent information  
F. FQDN  
Answer: BC  
QUESTION 114 Which statement about Cisco ISE BYOD is true?  
A. Dual SSID allows EAP-TLS only when connecting to the secured SSID.  
B. Single SSID does not require endpoints to be registered.  
C. Dual SSID allows BYOD for guest users.  
D. Single SSID utilizes open SSID to accommodate different types of users.  
E. Single SSID allows PEAP-MSCHAPv2 for native supplicant provisioning.  
Answer: E  
QUESTION 115 Which two types of client provisioning resources are used for BYOD implementations? (Choose two.)  
A. user agent  
B. Cisco NAC agent  
C. native supplicant profiles  
D. device sensor  
E. software provisioning wizards  
Answer: CE  
QUESTION 116 Which protocol sends authentication and accounting in different requests?  
A. RADIUS  
B. TACACS+  
C. EAP-Chaining  
D. PEAP  
E. EAP-TLS  
Answer: B  
QUESTION 117 You enabled the guest session limit feature on the Cisco ISE. However, end users report that the same guest can log in from multiple devices simultaneously. Which configuration is missing on the network access device?  
A. RADIUS authentication  
B. RADIUS accounting  
C. DHCP required  
D. AAA override  
Answer: B  
**!!!RECOMMEND!!!**1.|2018 New 300-208 Exam Dumps (PDF 7 VCE) 320Q&As Download:  
<https://www.braindump2go.com/300-208.html>2.|2018 New 300-208 Study Guide Video: YouTube Video:  
[YouTube.com/watch?v=yYAD1q-JEEY](https://www.youtube.com/watch?v=yYAD1q-JEEY)