Official New Updated 350-080 Exam Questions and Answers Shared By Braindump2go For Free Download Today! (251-260)

CISCIO NEW UPDATED: New Updated 350-080 Exam Questions from Braindump2go 350-080 PDF Dumps and 350-080 VCE Dumps! Welcome to Download the Newest Braindump2go 350-080 VCE&PDF Dumps: http://www.braindump2go.com/350-080.html (394 Q&As) Cisco Official Exam Center New Released 350-080 Dumps Questions, Many New Questions added into it! Braindump2go Offer Free Sample Questions and Answers for Download Now! Visit Our Webiste, get the new updated Questions then pass Cisco 350-080 at the first try! Vendor: CiscoExam Code: 350-080Exam Name: CCIE Data Center Written Exam350-080 Dumps,350-080 Exam Dumps,350-080 Brainfump,350-080 Questions,350-080 VCE,350-080 PDF,350-080 Actual Test,350-080 Study Guide,350-080 Book,350-080 CCIE Data Center Written Exam,350-080 Test

QUESTION 251Refer to the exhibit. Which two statements about the output and diagram are true? (Choose two.)

A. FI-A is configured in FC switch mode.B. VSAN trunking is enabled on FI-A.C. The native VSAN should be VSAN 1.D. Cisco UCS will allow all VSANs by default when FC trunking is enabled.E. FI-A requires VSAN pruning.F. Interface fc1/8 on MDS-A should be configured as a TE Port. Answer: BD QUESTION 252You are about to assign a static UUID to a service profile. This particular UUID is also defined within the range of a UUID pool. The duplicate UUID in the pool has not yet been allocated. What will be the result of applying the static UUID? A. Applying the static UUID will fail with an error stating that the UUID exists within a defined resource pool.B. Applying the static UUID will succeed with no warnings.C. Applying the static UUID will succeed and a minor fault will be raised.D. Applying the static UUID will succeed and an information fault will be raised.E. Applying the static UUID will fail with an error stating that the UUID is a duplicate UUID. Answer: B QUESTION 253What is the purpose of the management interface monitoring policy? A. to monitor the management interface counters for errors and dropsB. to prevent VM traffic from being black-holed during a cluster switchoverC. to sync MAC address tables between peer fabric interconnectsD. to ensure that the management interface of the managing fabric interconnect can reach the gateway Answer: D QUESTION 254How many traffic monitoring sessions can you create on Cisco UCS Manager? A. 16B. 8C. 24D. 32 Answer: A QUESTION 255Fault suppression allows you to suppress SNMP trap and Call Home notifications during a planned maintenance period. Which three commands are necessary to activate these suppression polices in Cisco UCS Manager? (Choose three.) A. default-chassis-all-maintB. default-chassis-phys-maintC. default-fex-all-maintD. default-FI-phys-maintE. default-blade-phys-maintF. default-vic-phys-maint Answer: ABC QUESTION 256Refer to the exhibit. Assume that there is no disjoint Layer 2 configuration. Based on the output, what will happen if uplink eth1/7 on FI-A fails?

A.   The host will lose Ethernet uplink connectivity on FI-A.B.   Fabric failover will force the vNIC that is bound to FI-A to use uplink eth1/7 on FI-B.C.   Cisco UCS Manager will disable the host vNIC that is connected to FI-A.D.   Traffic from any hosts using this pin group will use e1/8 on FI-A. Answer: D QUESTION 257A load balancer performs an operation on a predefined parameter, such as the IP address, HTTP cookie, or URL, when a new connection is made so that another connection with the same parameter will always reach the same server. Which load-balancing predictor does this statement describe? A.   round robinB.   least-connectionsC.   hashingD.   least-loaded Answer: C QUESTION 258Refer to the exhibit. Which two statements about the exhibit are true? (Choose two.)

A.   The domain ID for SAN A is 0x64.B.   fc1/8 and fc1/9 on the MDS-A are configured as E Ports.C.   fc1/8 and fc1/9 on the MDS-A are configured as TE Ports.D.   fc1/8 and fc1/9 on the MDS-A are configured as F Ports.E.   FC trunking is enabled on the Fabric Interconnect.F.   The domain ID for SAN A is 0x640. Answer: AD QUESTION 259Which three options are valid ACE probes? (Choose three.) A.   HTTPB.   TelnetC.   Java scriptingD.   TCL scriptingE.   XML scriptingF.   SSH Answer: ABD QUESTION 260Refer to the exhibit. Based on the output, what is the most likely reason for the failure of the iSCSI boot?

A.   There is no gateway configured on the iSCSI vNIC.B.   The LUN is not masked correctly on the storage array.C.   CHAP authentication is not configured correctly.D.   The latency between the imitator and target is too high. Answer: B   350-080 Updated Questions are 2015 Latest Released Which 100% will Meet in Your 350-080 Test! Braindump2go New Released 350-080 Exam Dumps Contain All New Added Questions Which Will Help you Have A Totally Success in 2015 New Tear! Download our 100% Pass Guaranteed 350-080 Exam Dumps Full Version, special 10% Off Discount enjoyed!

FREE DOWNLOAD: NEW UPDATED 350-080 PDF Dumps & 350-080 VCE Dumps from Braindump2go:
http://www.braindump2go.com/350-080.html (394 Q&A)