

## [2016-Nov.-NewExam Pass 100% !CCNP 300-101 VCE and 300-101 VCE 230q Instant Download[NQ194-NQ212]

2016/11 New CCNP Routing and Switching 300-101 ROUTE: Implementing Cisco IP Routing (ROUTE) Exam Questions Updated Today! 1.|2016.Nov. 300-101 Exam Dumps (PDF & VCE) 230Q&As Download:<http://www.braindump2go.com/300-101.html>  
2.|2016.Nov. 300-101 Exam Questions & Answers:<https://1drv.ms/b/s!AvI7wzKf6QBjgQU3MiuxP2dJi8Wo> QUESTION 184What command can you enter to configure an enable password that uses an encrypted passwordfrom another configuration? A. enable secret \$abc%!e.Cd34\$!ao0B. enable secret 7 Sabc%!e.Cd34\$!ao0C. enable secret 0 Sabc%U\*.Cd34\$!ao0D. enable secret 5 \$abc%!e.Cd34\$!ao0E. enable secret 15 \$abc%ie.Cd34\$!ao0F. enable secret 6 \$abc%!e.Cd34\$!ao0 Answer: D QUESTION 185 A network engineer receives reports about poor voice quality issues at a remote site. The network engineer does a packet capture and sees out-of-order packets being delivered. Which option can cause the VOIP quality to suffer? A. traffic over backup redundant linksB. misconfigured voice vlanC. speed duplex link issuesD. load balancing over redundant links Answer: DExplanation:In traditional packet forwarding systems, using different paths have varying latencies that cause out of order packets,eventually resulting in far lower performance for the network application. Also , if some packets are process switched quickly by the routing engine of the router while others are interrupt switched (which takes more time)then it could result in out of order packets. The other options would cause packet drops or latency, but not out of order packets. QUESTION 186What is the administrative distance for EBGP? A. 200B. 30C. 70D. 20 Answer: D QUESTION 187Considering the IPv6 address independence requirements, which process do you avoid when you use NPTv6 for translation? A. rewriting of higher layer informationB. checksum verificationC. ipv6 duplication and conservationD. IPSEC AH header modification Answer: AExplanation:The IPv6-to-IPv6 Network Prefix Translation (NPTv6) serves as a useful mechanism for implementing address independence in an IPv6 environment. A major benefit associated with NPTv6 is the fact that it avoids the requirement for an NPTv6 Translator to rewrite the transport layer headers which reduces the load on network devices

[http://www.cisco.com/c/en/us/td/docs/ios-xml/ios/ipaddr\\_nat/configuration/xe-16/nat-xe-16-book/iadnat-asr1k-nptv6.html](http://www.cisco.com/c/en/us/td/docs/ios-xml/ios/ipaddr_nat/configuration/xe-16/nat-xe-16-book/iadnat-asr1k-nptv6.html)

QUESTION 188What is the optimal location from which to execute a debug command that produces an excessiveamount of information? A. Vty linesB. SNMP commandsC. A console portD. An AUX port Answer: AExplanation:

<http://www.cisco.com/c/en/us/support/docs/dial-access/integrated-services-digital-networks-isdn-channel-associated-signaling-cas/10374-debug.html>

QUESTION 189A network engineer is configuring the router for NetFlow data exporting.What is required in orderfor NDE to begin exporting data? A. SourceB. Flow maskC. DestinationD. Interface type E. Traffic typeF. NetFlow version Answer: CExplanation:NetFlow Multiple Export Destinations--To configure redundant NDE data streams, which improves the probability of receiving complete NetFlow data, you can enter the ip flow-export destination command twice and configure a different destination IP address in each command. Configuring two destinations increases the RP CPU utilization, as you are exporting the data records twice.

[http://www.cisco.com/en/US/docs/general/Test/dwerblo/broken\\_guide/nde.html#wp1139278](http://www.cisco.com/en/US/docs/general/Test/dwerblo/broken_guide/nde.html#wp1139278) QUESTION 190Refer to the exhibit.

Router 1 cannot ping router 2 via the Frame Relay between them.Which two statements describe the problems? (Chooses two.) A.

Encapsulation is mismatched.B. Frame Relay map is configured.C. DLCI is active.D. DLCI is inactive or deleted.E. An

access list is needed to allow ping Answer: ADExplanation:Frame Relay: Cannot ping Remote Router :1-Encapsulation mismatch has occurred.2-DLCI is inactive or has been deleted.3-DLCI is assigned to the wrong subinterface.4-An access list was misconfigured.5-The frame-relay map command is missing.6-No broadcast keyword is found in frame-relay map statements.

QUESTION 191At which layer does Cisco Express Forwarding use adjacency tables to populate addressinginformation? A.

Layer4B. Layer 2C. Layer 1D. Layer 3 Answer: BExplanation:Adjacency table - Nodes in the network are said to be adjacent if they can reach each other with a single hop across a link layer. In addition to the FIB, CEF uses adjacency tables to prepend Layer 2 addressing information. The adjacency table maintains Layer 2 next-hop addresses for all FIB entries

<http://www.cisco.com/c/en/us/support/docs/routers/12000-series-routers/47321-ciscoef.html>

QUESTION 192A network engineer wants to ensure an optimal end-to-end delay bandwidth product. The delay isless than 64 KB. Which TCP feature ensures steady state throughput? A. Window scalingB. Network buffersC. Round-trip timersD. TCP acknowledgments Answer: AExplanation:options can be carried in a TCP header. Those relevant to TCP performance include Window-scale option : This option is intended to address the issue of the maximum window size in the face of paths that exhibit a high-delay bandwidth product. This option allows the window size advertisement to be right-shifted by the amount specified (in binary arithmetic, a right-shift corresponds to a multiplication by2). Without this option, the maximum window size that can be advertised is 65,535 bytes (the maximum value obtainable in a 16-bit field). The limit of TCP transfer speed is effectively one window size in transit between the

sender and the receiver. For high-speed, long-delay networks, this performance limitation is a significant factor, because it limits the transfer rate to at most 65,535 bytes per round-trip interval, regardless of available network capacity. Use of the window-scale option allows the TCP sender to effectively adapt to high-band-width, high-delay network paths, by allowing more data to be held in flight. The maximum window size with this option

<http://www.cisco.com/c/en/us/about/press/internet-protocol-journal/back-issues/table-contents-5/>

ipj-archive/article09186a00800c8417.html QUESTION 193A network administrator creates a static route that points directly to a multi-access interface, instead of the next-hop IP address. The administrator notices that Cisco Express Forwarding ARP requests are being sent to all destinations. Which issue might this configuration create? A. Low bandwidth usageB. High memory usageC.

Cisco Express Forwarding routing loopD. High bandwidth usageE. IP route interference Answer: CExplanation:

<http://www.cisco.com/c/en/us/support/docs/ip/express-forwarding-cef/26083-trouble-cef.html> QUESTION 194Refer to the exhibit.

Which three NTP features can be deduced on the router? (choose three)

! ! !  
ntp access group peer 2  
**Braindump2go.com**  
ntp master 4  
!

! ! !  
access-list 1 permit 192.168.1.1  
access-list 1 deny any  
access-list 2 permit 192.168.1.1  
access-list 2 deny any  
!

A. only accepts time requests from 192.168.1.1B. only handle four requests at a timeC. only is in stratum 4D. only updates its time from 192.168.1.1E. only accepts time requests from 192.168.1.4F. only updates its time from 192.168.1.4 Answer: ACF Explanation: IOS router defines the following four types of access for NTP: 1) Peer - permits router to respond to NTP requests and accept NTP updates. NTP control queries are also accepted. This is the only class which allows a router to be synchronized by other devices. 2) Serve - permits router to reply to NTP requests, but rejects NTP updates (e.g. replies from a server or update packets from a peer). Control queries are also permitted. 3) Serve-only - permits router to respond to NTP requests only. Rejects attempt to synchronize local system time, and does not access control queries. 4) Query-only - only accepts NTP control queries. No response to NTP requests are sent, and no local system time synchronization with remote system is permitted. QUESTION 212Refer to the exhibit. A network engineer is troubleshooting a DMVPN setup between the hub and the spoke. The engineer executes the command show crypto isakmp sa and observes the output that is displayed. What is the problem?

! ! !  
Braindump2go.com















B. That ISAKMP is using default settingsC. An incompatible IP sec transform setD. An incompatible ISAKMP policy

Answer: BExplanation:

<http://www.cisco.com/c/en/us/support/docs/security-vpn/ipsec-negotiation-ike-protocols/5409-ipsec-debug-00.html>

!!!RECOMMEND!!! 1.Braindump2go|2016.Nov. 300-101 Exam Dumps (PDF & VCE) 230Q&As Download:

<http://www.braindump2go.com/300-101.html> 2.Braindump2go|2016.Nov. 300-101 Exam Questions & Answers:

<https://1drv.ms/b/s!AvI7wzKf6QBjgQU3MiuxP2dJi8Wo>