

[2016-Sep.-NewBraindump2go 400-201 Exam VCE and PDF 414q&as [NQ21-N30 Download

2016.09 New 400-201: Cisco CCIE Service Provider Written Exam v4.1 Exam Questions Updated Today! Free Download 400-201 Exam Dumps(PDF & VCE) 414Q&As from Braindump2go.com Today!100% Real Exam Questions! 100% Exam Pass Guaranteed! **NEW QUESTION 21 - NEW QUESTION 30** 1.[2016 New 400-201 Exam Dumps(PDF & VCE) 414Q&As Download:<http://www.braindump2go.com/400-201.html>2.[2016 New 400-201 Exam Questions & Answers:<https://drive.google.com/folderview?id=0B75b5xYLjSSNRjJsZE5Fd04xYTQ&usp=sharing> **QUESTION 21**What IOS commands display MPLS label mapping on an LSR? A. Show mpls ldp parametersB. Show mpls ldp bindingsC. Show mpls forwarding-tableD. Show mpls ldp discoveryE. Show mpls ldp neighbor detail Answer: B **QUESTION 22**Drag and Drop Questions

Drag and drop the appropriate VRF description on the left to the corresponding identifier on the right.

VRF4	1/1
VRF5	2/1
VRF3	2/2R
VRF Unicast	2/2D

Answer:

Drag and drop the appropriate VRF description on the left to the corresponding identifier on the right.

VRF4	VRF Unicast
VRF5	VRF4
VRF3	VRF5
VRF Unicast	VRF3

QUESTION 23Refer to the exhibit. The vrf MAINT has been provisioned and used by the Service Provider management network. The engineer discovers that syslog messages are not being received on the syslog server. IP reachability has been validated using ping. Which issue in the configuration must be corrected?

```
Router PE-1

config t
ip vrf MAINT
rd 200:1
route-target import 100:1
route-target export 100:1
exit
!
ip vrf forwarding MAINT
ip address 10.10.100.2 255.255.255.0
no shut
exit
!
logging on
logging host 10.10.100.100
logging trap debugging
end
```

A. logging on must include the vrf MAINT keyword.B. logging host must include the vrf MAINT keyword.C. The logging facility must be configured for syslog processing.D. The route targets that are configured do not match the route distinguisher.

Answer: BExplanation:http://www.cisco.com/c/en/us/td/docs/ios/12_2sr/12_2sra/feature/guide/srvrflg.html#wp10 59076

QUESTION 24Which are the three header fields that affect how Equal-Cost Multipath hashes traffic flow into interface groups?

(Choose three.) A. source MAC addressB. source portC. source IP addressD. destination IP addressE. IP protocol

IDF. destination MAC address Answer: BCD **QUESTION 25**An R1 router requires an equal load balancing to reach the prefix

192.168.0.0/16 over two exit points: through R2 and R3 routers. Which two options must be configured on the R1 router to achieve

this goal? (Choose two.) A. The BGP maximum path feature must be configured on R1.B. The BGP PIC core must be enabled

on R1C. Weight, local-pref, MED, as-path length, origin, and the BGP next-hop IGP cost must be the same for the R2 and R3

IBGP updates to R1.D. The BGP Link Bandwidth feature must be applied on R1.E. BGP extended community exchange must be

enabled between IBGP neighbors. Answer: ACEExplanation:BGP link-bandwidth is for unequal-cost routes. **QUESTION 26**A

company is deciding between an HVR and SVR solution in order to finalize a virtualization project proposal. Which is an advantage

of a HVR solution versus a SVR solution? A. A HVR solution implements dedicated data plane resources.B. A HVR solution

implements shared control plane resources.C. A HVR solution introduces significant contention of resources.D. A HVR solution implements dedicated chassis resources. Answer: AExplanation:

http://www.cisco.com/en/US/solutions/collateral/ns341/ns524/ns562/ns573/white_paper_c11-512753_ns573_Networking_Solutions_White_Paper.html QUESTION 27Which three of these are optical channel data unit (ODU) overhead fields? (Choose three) A.

general communication channel 0 (GCC0)B. section monitoringC. reserved (RES)D. general communication channels 1 and 2 (GCC1 GCC2)E. tandem connection monitoring activation deactivation (TCM ACT) Answer: CDE QUESTION 28Which three

modes are the operating of HDLC? (Choose three) A. asynchronous balanced mode (ABM)B. normal response mode (NRM)C. normal peer mode (NPM)D. asynchronous client mode (ACM)E. asynchronous response mode (ARM) Answer: ABE

Explanation: Asynchronous response mode is an HDLC addition[1] for use over full-duplex links. While retaining the primary/secondary distinction, it allows the secondary to transmit at any time. Asynchronous balanced mode added the concept of a combined terminal which can act as both a primary and a secondary. There are some subtleties about this mode of operation; while many features of the protocol do not care whether they are in a command or response frame, some do, and the address field of a received frame must be examined to determine whether it contains a command (the address received is ours) or a response (the address received is that of the other terminal). QUESTION 29BGP best route selection process is based on what? A. path attributes B. lowest costC. highest bandwidthD. lowest delayE. lowest hop-count Answer: A QUESTION 30Refer to the exhibit. In the short-pipe QoS mode, this customer has QoS control for which two links? (Choose two.)



A. aB. cC. dD. bE. e Answer: AE **!!!RECOMMEND!!!** 1.Braindump2go|2016 New 400-201 PDF & 400-201 VCE 414Q&As Download: <http://www.braindump2go.com/400-201.html> 2.Braindump2go|2016 New 400-201 Questions & Answers: <https://drive.google.com/folderview?id=0B75b5xYLjSSNRjJsZE5Fd04xYTQ&usp=sharing>