[2017-New-Version!100% Valid Cisco 400-101 PDF and VCE Dumps 256Q Provided by Braindump2go[168-178

2017 Feb. New 400-101 Exam Questions Updated in www.Braindump2go.com Today! 1.|NEW 400-101 Exam Dumps (PDF & VCE) 222Q&As Download:http://www.braindump2go.com/2v0-621d.html2.|NEW 400-101 Exam Questions & Answers Download:https://ldrv.ms/b/s!AvI7wzKf6OBjgwMdv2eEddffAn0i OUESTION 168Which command can you enter to disable logging for VTY lines? A. no logging monitorB. no logging countC. no logging bufferD. no logging consoleE. no logging trap Answer: D QUESTION 169Which feature monitors network events and takes automated action based on scripts configured by the administrator? A. NetFlowB. Performance MonitoringC. EPCD. EEM Answer: D QUESTION 170Which IPv4 feature prevents multicast joins on a per-port basis? A. MLD filteringB. IGMP snoopingC. IGMP filteringD. PIM snooping Answer: B QUESTION 171Which two statements about PfR are true?(Choose two) A. It manages traffic classesB. It provides a narrower scope of route control than OER.C. It provides intelligent route control on a per-application basis.D. It supports split tunneling and spoke-to-spoke links.E. It always prefers the least cost path. Answer: AE QUESTION 172Which statement about EIGRP request packets is true? A. They determine whether a destination is reachableB. They are transmitted unreliablyC. They are transmitted via broadcastD. They are sent in response to queries Answer: B QUESTION 173Which routing protocol is not supported with VRF-lite? A. IS-ISB. OSPFC. EIGRPD. BGP Answer: A QUESTION 174How can you reduce latency on a VoIP network? A. Implement a congestion-avoidance algorithmB. Implement low latency queuingC. Configure an SLA to collect information on packet lossD. Set the IP SLA timeout to 1000 milliseconds.E. Implement fast retransmission. Answer: B QUESTION 175Which two statements about the host address 172.150.100.10/18 are true?(Choose two) A. The network address is 172.150.0.0B. The network address is 172.150.64.0C. The network address is 172.150.100.0D. The broadcast address is 172.150.127.255E. The broadcast address is 172.150.255.255F. The broadcast address is 172.150.100.255 Answer: BD QUESTION 176Refer to the exhibit. What are two effects of the given configuration?(Choose two) interface FastEthernet0/0

nterface FastEthernet0/0 ip address 192.168.12.1 255.255.25

passive-interface FastEthernet0/0 network 192.168.12.0 no auto-summary

A. The router will fail to form neighbor adjacencies over all EIGRP interfaces except F0/0B. The router will fail to form neighbor adjacencies over interface F0/0C. The router will advertise the 192.168.12.0/27 networkD. The router will manuallu summarize the 192.168.12.0/27 networkE. Auto-summarization will be enabled on the F0/0 interface Answer: BC QUESTION 177Which two statements about IPv6 PIM are true?(Choose two) A. PIM-SM and PIM-SSM can be configured in the same networkB. PIM-SM bases its RPF checks on the unicast routing tableC. It supports both sparse mode and dense modeD. It supports both Auto-RP and BSRE. It works in conjunction with unicast routing protocols to send and receive multicast updates Answer: AB QUESTION 178Wht is the EUI 64-bit address corresponding to MAC address 0032F4C57781? A. FFFE0032F4C57781B. 0032F4FFFEC57781C. 0032F4C57781FFFED. C57781FFFE0032F4 Answer: B

!!!RECOMMEND!!! 1.|NEW 400-101 Exam Dumps (PDF & VCE) 222Q&As Download: http://www.braindump2go.com/2v0-621d.html 2.|NEW 400-101 Study Guide Video: YouTube Video: YouTube.com/watch?v=ZCPWibGcLDA

Braindump