[2018-April-New100% Valid 352-001 VCE Dumps 510Q Provided by Braindump2go[221-231

2018 April Latest Cisco 352-001 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 352-001 Real Exam Questions: 1.|2018 Latest Cisco 352-001 Exam Dumps (PDF & VCE) 510Q

Download:https://www.braindump2go.com/352-001.html2.|2018 Latest Cisco 352-001 Exam Questions & Answers Download:https://drive.google.com/drive/folders/0B75b5xYLjSSNSUNBNi1aYkpfOTQ?usp=sharingQUESTION 221Why should IGP advertisements be disabled on an access link where a host is attached?A. because hosts do not run routing protocolsB. prevent the injection of bad routes C. to reduce router overhead D. because edge hosts are statically routed Answer: BQUESTION 222In a PIM sparse mode network, how is the flow of multicast traffic restored when a link fails along a branch of a multicast distribution tree?A. The downstream receivers notice the loss of the multicast flow and resend PIM join messages to reestablish the tree.B. The downstream receivers notice the loss of the multicast flow and resend IGMP Membership Reports to reestablish the tree.C. The traffic reverts to the shared tree while the downstream router recalculates the RPF interface and sends a new PIM join message to the RP.D. The router downstream of the break recalculates the RPF interface when it notices a change in the unicast routing table and immediately sends a new PIM join message out from the new RPF. Answer: DQUESTION 223A service provider is offering a QoS-based transport service. Three classes have been defined in the core, including an Expedited Forwarding (EF) class for VoIP traffic. Which tool should be used at the ingress for the EF class? A. policing B. shaping C. WREDD. CB-WFQ **Answer:** AQUESTION 224What is downstream suppression?A. the ability of a fault management tool to generate alerts for only an upstream device failure and to suppress the alarms related to all unreachable downstream sites B. the ability of devices to exclusively send summary routes and suppress the sending of complete routing updatesC. the ability of a router to suppress downstream route fluctuations to avoid introducing instability into the network coreD. the ability of a network management station to perform root cause analysis on a network fault and remove duplicates of all other alarms resulting from fault symptomsE. the ability of an element manager to restrict forwarding to critical performance alarms northbound to the Manager of Managers and suppress other alarms Answer: AQUESTION 225 Which of these statements accurately describes MPLS-based L3VPN service? A. It allows for transparent routing across the service provider.B. It offloads routing between sites to the service provider.C. It is independent of the routed protocol.D. It improves routing protocols and network convergence. Answer: BOUESTION 226Refer to the exhibit. Which configuration change would maximize the efficiency of both the routing design and data forwarding plane in this topology? A. configure Router B to advertise the more specific prefixes instead of the aggregateB. configure Router B to advertise the more specific prefixes in addition to the aggregateC. configure Router B with a static route for the aggregate to Null0 D. configure Router A to advertise 10.0.0.0/8 instead of the default route to Router BAnswer: CQUESTION 227An enterprise has a large number of retail locations that are currently serviced by a hub-and-spoke Frame Relay network using OSPF as the routing protocol. The enterprise is planning to deploy a high-bandwidth application that requires any-to-any connectivity. Which technology would provide this enterprise with the best bandwidth utilization and greatest scalability? A. pseudowires based on L2TPv3B. multipoint GRE tunnels between all locationsC. a full mesh of IPsec tunnels between all locationsD. L3VPNs (RFC 2547-based) using MP-BGPAnswer: DQUESTION 228A service provider has an MPLS VPN network in the United States. It recently bought another provider in India and wants to quickly integrate the newly acquired provider's network into the existing MPLS VPN infrastructure via the Internet. Which two technologies can the service provider use to integrate its new network? (Choose two.) A. MPLS over L2TPv3B. MPLS over GREC. MPLS over IPsecD. MPLS based VPWSE. MPLS over IPv6Answer: AB QUESTION 229A certain service provider offers RFC 2547-based L3VPN service. The service provider is using OSPF to carry infrastructure routes and MP-BGP to carry customer routes. It has also deployed a full mesh of Cisco MPLS TE tunnels with FRR for link and node protection. OSPF and BGP have not been tuned for faster convergence. Which three types of failure does Cisco MPLS TE FRR address in this service provider's network? (Choose three.)A. P (core) node failureB. PE node failureC. PE-P link failureD. P-P link failureE. PE-CE link failureAnswer: ACDQUESTION 230Four routers running IS-IS are connected to a single Ethernet link. Then, a fifth router is connected, which has a priority higher than any of the other routers connected to the network. What will happen? A. The new router will become the DIS and cause a temporary disruption in traffic through the link. B. The new router will become the DIS without causing a temporary disruption in traffic through the link.C. The new router will not be elected DIS unless the current DIS fails.D. The new router will not be elected DIS unless it has the lowest NET ID.Answer: B QUESTION 231Which tool enables a network designer to route traffic based on the source IP address? A. source routing B. MPLS Layer 3 VPNsC. policy-based routingD. unicast Reverse Path ForwardingAnswer: C!!!!RECOMMEND!!!!1.|2018 Latest Cisco 210-260 Exam Dumps (PDF & VCE) 510Q Download:https://www.braindump2go.com/352-001.html2.|2018 Latest

Cisco 210-260 Exam Study Guide: YouTube Video: YouTube.com/watch?v=IvDhpfzNdP0