

## [August-2019-NewExam 300-115 Dumps VCE Format Free from Braindump2go

August/2019 Braindump2go 300-115 Exam Dumps with PDF and VCE New Updated Today! Following are some 300-115 Real Exam Questions:1.|2019 Latest Braindump2go 300-115 Exam Dumps (PDF & VCE) Instant

Download:<https://www.braindump2go.com/300-115.html>2.|2019 Latest Braindump2go 300-115 Exam Questions & Answers Instant

Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNYjV4eHQ4dTJoQXc?usp=sharing>Real QuestionsA question on local database for consoling to network devices.A. Local user dbs can be main and also backup authentication methodB. Local user dbs is the only backup authentication methodC. You can set user privileged levelsD. Local user dbs is used after 3 unsuccessful logins via Radius server Correct Answer:**Answer: AC**Real QuestionsThree reasons for err-disable. (Choose three)A. configuration ports into EtherChannelB. storm controlC. security violationD. Not availableE. Not availableF. BPDUGuardAnswer: BCFExplanation:There are various reasons for the interface to go into errdisable. The reason can be:- A cable that is out of specification (either too long, the wrong type, or defective)- Bad network interface card (NIC) card (with physical problems or driver problems)- Port duplex misconfiguration- Duplex mismatch- Port channel misconfiguration- BPDU guard violation- UniDirectional Link Detection (UDLD) condition- Late-collision detection- Link-flap detection- Security violation- Port Aggregation Protocol (PAgP) flap- Layer 2 Tunneling Protocol (L2TP) guard- DHCP snooping rate-limit- Incorrect GBIC / Small Form-Factor Pluggable (SFP) module or cable- Address Resolution Protocol (ARP) inspection- Inline power- Storm ControlReal Questionsquestion in regards to what would occur after implementing RSPAN on a switch.A. Not AvailableB. Traffic in network is doubledC. Not AvailableD. Destination port is unusable for normal use**Answer: D**Real QuestionsWhich switchport feature will block the packet with unknown MAC address from sending it via portA. Switchport block unicastB. Packet with unknown MAC will be droppedC. Switchport portfastD. Switchport protect**Answer: A**Real QuestionsWhat are the two ways to configure loop guard?A. (config)# spanning-tree loopguard defaultB. (config-if)# spanning-tree guard loopC. (config)# spanning-tree loopguard enableD. (config-if)# spanning-tree loopguard defaultE. (config)# spanning-tree guard loopAnswer: AB

Explanation:[https://www.cisco.com/c/en/us/support/docs/lan-switching/spanning-tree-protocol/10596-84.html#loop\\_guard](https://www.cisco.com/c/en/us/support/docs/lan-switching/spanning-tree-protocol/10596-84.html#loop_guard)Real QuestionsQuestion about action of DAI with invalid IP-to-MAC.A. InterceptB. DropsC. LogD. NAA**Answer: ABC**Real QuestionsQuestion about what are RADIUS server responsesA. AcceptB. RejectC. ChallengeD. Get PasswordE. Cancel**Answer: ABC**Real QuestionsWhat happens if a switch with dhcp snooping and ip source guard enabled globally, what does the switch do when it receives a packet with option 82?A. DropB. Remove 82 and forwardC. ProxyD. NAA**Answer: B**Explanation:The switch removes the option-82 field and forwards the packet to the switch port that connects to the DHCP client that sent the DHCP request.

[http://www.cisco.com/c/en/us/td/docs/switches/lan/catalyst3850/software/release/3se/security/configuration\\_guide/b\\_sec\\_3se\\_3850\\_cg/b\\_sec\\_3se\\_3850\\_cg\\_chapter\\_01100.html](http://www.cisco.com/c/en/us/td/docs/switches/lan/catalyst3850/software/release/3se/security/configuration_guide/b_sec_3se_3850_cg/b_sec_3se_3850_cg_chapter_01100.html)Real QuestionsWhich two statements are true about Option 82? (Choose two.)A. Layer 2 ingressB. Layer 3 egressC. Layer 3 ingressD. Layer 2 egressE. Layer 4 egressF. Layer 4 ingress**Answer: AB**Explanation:Layer 2 ingress - "Enters interface configuration mode, where slot/port is the Layer 2 Ethernet ingress interface where you want to configure the option 82 string." (see "Enabling or Disabling Option 82 User Defined Data Insertion and Removal") <<ingress (in) Layer 3 egress - this sounds right";Enters interface configuration mode, where slot/port is the interface for which you want to enable or disable subnet broadcast support for the DHCP relay agent. (see "Enabling or Disabling Subnet Broadcast Support for the DHCP Relay Agent on a Layer 3 Interface") <<egress (out)

[http://www.cisco.com/c/en/us/td/docs/switches/datacenter/nexus3548/sw/security/6-x/b\\_N3548\\_Security\\_Config\\_602\\_A11/b\\_N3548\\_Security\\_Config\\_602\\_A11\\_chapter\\_01011.html](http://www.cisco.com/c/en/us/td/docs/switches/datacenter/nexus3548/sw/security/6-x/b_N3548_Security_Config_602_A11/b_N3548_Security_Config_602_A11_chapter_01011.html)Real QuestionsWhich three functions does Dynamic ARP Inspection perform with invalid IP-to-MAC address bindings?A. deletesB. logsC. acceptsD. interceptsE. discardsF. bypasses**Answer: BDE**Real QuestionsWhich three features can be optimized by using SDM templates?A. port securityB. trunkC. VLAN.D. accessE. DHCP snoopingF. routing**Answer: CDE**!!!RECOMMEND!!!1.|2019 Latest Braindump2go 300-115 Exam Dumps (PDF & VCE) Instant Download:<https://www.braindump2go.com/300-115.html>2.|2019 Latest Braindump2go 300-115 Study Guide Video Instant Download: YouTube Video: [YouTube.com/watch?v=xiEJpkhDHk8](https://www.youtube.com/watch?v=xiEJpkhDHk8)