

## [Dec.-2016-NewValid Braindump2go Cisco 300-115 Braindumps PDF 230q Offer[51-60

2016 Dec. New Cisco 300-115: Implementing Cisco IP Switched Networks (SWITCH v2.0) Exam Questions Updated Today!Free Instant Download 300-115 Exam Dumps (PDF & VCE) 230q download from Braindump2go.com Today! 100% Real Exam Questions! 100% Exam Pass Guaranteed! 1.|2016 Dec. New 300-115 Exam Dumps (PDF & VCE) 230q download: <http://www.braindump2go.com/300-115.html>2.|2016 Dec. New 300-115 Exam Questions & Answers: <https://1drv.ms/f/s!AvI7wzKf6QBjgSVgicAB52AMWrK2> QUESTION 51What is the size of the VLAN field inside an 802.1q frame? A. 8-bitB. 12-bitC. 16-bitD. 32-bit Answer: B QUESTION 52What is the maximum number of VLANs that can be assigned to an access switchport without a voice VLAN? A. 0B. 1C. 2D. 1024 Answer: B QUESTION 53Refer to the exhibit. Which option shows the expected result if a show vlan command is issued?

```
Interface GigabitEthernet1/0/1
switchport access vlan 10
switchport trunk encapsulation dot1q
switchport mode trunk
switchport voice vlan 11
spanning-tree portfast
!
```

A.

VLAN Name	Status	Ports
1 default	active	G11/0/2, G11/0/3, G11/0/4 G11/0/5, G11/0/6, G11/0/7 G11/0/8, G11/0/9, G11/0/10 G11/0/11, G11/0/12, G11/0/13 G11/0/14, G11/0/15, G11/0/16 G11/0/17, G11/0/18, G11/0/19 G11/0/20, G11/0/21, G11/0/22 G11/0/23, G11/0/24
10 Data	active	
11 voice	active	G11/0/1
1002 fddi-default	act/unsup	
1003 token-ring-default	act/unsup	
1004 fddinet-default	act/unsup	
1005 trnet-default	act/unsup	

B.

VLAN Name	Status	Ports
1 default	active	G11/0/2, G11/0/3, G11/0/4 G11/0/5, G11/0/6, G11/0/7 G11/0/8, G11/0/9, G11/0/10 G11/0/11, G11/0/12, G11/0/13 G11/0/14, G11/0/15, G11/0/16 G11/0/17, G11/0/18, G11/0/19 G11/0/20, G11/0/21, G11/0/22 G11/0/23, G11/0/24
10 Data	active	G11/0/1
11 voice	active	G11/0/1
1002 fddi-default	act/unsup	
1003 token-ring-default	act/unsup	
1004 fddinet-default	act/unsup	
1005 trnet-default	act/unsup	

C.

VLAN Name	Status	Ports
1 default	active	G11/0/2, G11/0/3, G11/0/4 G11/0/5, G11/0/6, G11/0/7 G11/0/8, G11/0/9, G11/0/10 G11/0/11, G11/0/12, G11/0/13 G11/0/14, G11/0/15, G11/0/16 G11/0/17, G11/0/18, G11/0/19 G11/0/20, G11/0/21, G11/0/22 G11/0/23, G11/0/24
10 Data	active	G11/0/1
11 voice	active	G11/0/1
1002 fddi-default	act/unsup	
1003 token-ring-default	act/unsup	
1004 fddinet-default	act/unsup	
1005 trnet-default	act/unsup	

D.

VLAN Name	Status	Ports
1 default	active	G11/0/2, G11/0/3, G11/0/4 G11/0/5, G11/0/6, G11/0/7 G11/0/8, G11/0/9, G11/0/10 G11/0/11, G11/0/12, G11/0/13 G11/0/14, G11/0/15, G11/0/16 G11/0/17, G11/0/18, G11/0/19 G11/0/20, G11/0/21, G11/0/22 G11/0/23, G11/0/24
10 Data	active	G11/0/1
11 voice	active	G11/0/1
1002 fddi-default	act/unsup	
1003 token-ring-default	act/unsup	
1004 fddinet-default	act/unsup	
1005 trnet-default	act/unsup	

Answer: A QUESTION 54Which feature is automatically enabled when a voice VLAN is configured, but not automatically disabled when a voice VLAN is removed? A. portfastB. port-securityC. spanning treeD. storm control Answer: A QUESTION 55In which portion of the frame is the 802.1q header found? A. within the Ethernet headerB. within the Ethernet payloadC. within the Ethernet FCSD. within the Ethernet source MAC address Answer: A QUESTION 56Which VLAN range is eligible to be pruned when a network engineer enables VTP pruning on a switch? A. VLANs 1-1001B. VLANs 1-4094C. VLANs 2-1001D. VLANs 2-4094 Answer: C QUESTION 57Which action allows a network engineer to limit a default VLAN

from being propagated across all trunks? A. Upgrade to VTP version 3 for advanced feature set support.B. Enable VTP pruning on the VTP server.C. Manually prune default VLAN with switchport trunk allowed vlans remove.D. Use trunk pruning vlan 1.  
Answer: C QUESTION 58What is required for a LAN switch to support 802.1q Q-in-Q encapsulation? A. Support less than 1500 MTUB. Support 1504 MTU or higherC. Support 1522 layer 3 IP and IPX packetD. Support 1547 MTU only Answer: B

QUESTION 59Refer to the exhibit. How many bytes are added to each frame as a result of the configuration?

```
3512xl(config)#int fastEthernet 0/1
3512xl(config-if)#switchport mode trunk
3512xl(config-if)#switchport trunk
```

A. 4-bytes except the native VLANB. 8-bytes except the native VLANC. 4-bytes including native VLAN D. 8-bytes including native VLAN Answer: A QUESTION 60A network engineer configured a fault-tolerance link on Gigabit Ethernet links G0/1, G0/2, G0/3, and G0/4 between two switches using Ethernet port-channel. Which action allows interface G0/1 to always actively forward traffic in the port-channel? A. Configure G0/1 as half duplex and G0/2 as full duplex.B. Configure LACP port-priority on G0/1 to 1.C. Configure LACP port-priority on G0/1 to 65535.D. LACP traffic goes through G0/4 because it is the highest interface ID. Answer: B !!!RECOMMEND!!! 1.|2016 Dec. New 300-115 Exam Dumps (PDF & VCE) 230q download: <http://www.braindump2go.com/300-115.html>2.|2016 Dec. New 300-115 Exam Questions & Answers: YouTube Video: [YouTube.com/watch?v=dM4mTmskpfk](https://www.youtube.com/watch?v=dM4mTmskpfk)