[Dec-2018Free Cisco 430Q 300-208 VCE Dumps and 300-208 PDF Dumps Braindump2go Offer[Q399-409

<u>Dec/2018 Braindump2go 300-208 Exam Dumps with PDF and VCE New Updated Today! Following are some new 300-208 Real Exam Questions:</u>1.|2018 Latest 300-208 Exam Dumps (PDF & VCE) 430Q&As

Download:https://www.braindump2go.com/300-208.html2.|2018 Latest 300-208 Exam Questions & Answers Download:https://drive.google.com/drive/folders/0B75b5xYLjSSNdm14RFVqa0Q1YUU?usp=sharingQUESTION 399A wireless deployment must check guest device compliance before allowing access to the network. Which type of guest deployment is needed to allow the Client Provisioning portal? A. central web authentication B. sponsored C. hotspot D. self-registered Answer: B QUESTION 400Which characteristic of an 3GT enforcement policy is true?A. An SGFW has an implicit permit at the beginning. An SGFW has an implicit deny at the end.C. An SGACL has an implicit deny at the end.D. An SGACL has an explicit deny at the beginning. Answer: CQUESTION 401When configuring a BYOD portal, which two tasks must be completed? (Choose two.)A. Enable policy services.B. Create endpoint identity groupsC. Customize device portalsD. Create a client provisioning portal.E. Create external identity sources. Answer: AEQUESTION 402A customer has implemented a BYOD policy to allow employees to use personal devices on the corporate network. Which two methods can an employee use to add their devices to the network*? (Choose two.)A. Client Information SignalingB. My Device portalC. Client Handshake AuthenticationD. Helpdesk registrationE. native supplicants Answer: BDQUESTION 403Which type of probe is required when using a Cisco IOS Sensor-enabled network switch? A. network scan probeB. HTTP probeC. RADIUS probeD. NetFlow probeAnswer: D QUESTION 404An organization is deciding between single or dual SSID solutions for onboarding BYOD devices. Which item must be considered before selecting the dual SSID solution?A. Wireless coverage is reduced with dual SSIDsB. Additional access points are required for dual SSID.C. Dedicated controllers are required for dual SSIDs.D. The second SSID adds channel overhead Answer: BQUESTION 405 Which two values are compared by the binary comparison function in authentication that is based on Active Directory?A. subject alternative name and the common nameB. user-presented password hash and a hash stored in Active DirectoryC. user-presented certificate and a certificate stored in Active DirectoryD. MS-CHAPv2 provided machine credentials and credentials stored in Active Directory Answer: ADQUESTION 406A new consultant must be granted network access for only six months. Which type of ISE default guest account must be used to allow this access 1?A. contractorB. temporary C. employee D. annual Answer: A OUESTION 407Which two statements about RADIUS are true 1? (Choose two.) A. It uses UDP ports 1812 and 1813.B. It encrypts the payload.C. It encrypts the password onlyD. It uses TCP ports 1812 and 1813.E. It separates authorization and authentication functions Answer: ACQUESTION 408Which method of registering devices on the BYOD My Devices Portal requires that the user have a supplicant installed? A. MABB. single SS1DC. web authenticationD. dual SSIDAnswer: BQUESTION 409Which two options are advantages of using the Cisco IOS Device Sensor as compared to other profiling probes'? (Choose two.)A. uses RADIUS authentication messages to send gathered data to a Cisco ISE serverB. provides DHCP information to a Cisco ISE server without using an IP helper addressC. reduces the amount of traffic going to a Cisco ISE serverD. collects switch CPU and RAM usage for monitoring purposesE. replaces all the other profiling probes Answer: AD!!!RECOMMEND!!!1.|2018 Latest 300-208 Exam Dumps (PDF & VCE) 430Q&As Download:https://www.braindump2go.com/300-208.html2.|2018 Latest 300-208 Study Guide Video: YouTube Video: YouTube.com/watch?v=H1rA8 VAOhw