Jan/2019 Instant Download Braindump2go 400-351 Dumps PDF 502Q[Q172-Q182

January/2019 Braindump2go 400-351Exam Dumps with PDF and VCE New Updated Today! Following are some new 400-351 Real Exam Questions:]1.[2019 Latest 400-351 Exam Dumps (PDF & VCE) 502Q&As

Download:https://www.braindump2go.com/400-351.html2.|2019 Latest 400-351 Exam Questions & Answers Download: https://drive.google.com/drive/folders/0B75b5xYLjSSNa0JFbF9Gd3ZBU1E?usp=sharingQUESTION 172A user is presented with the underlying hardware and software needed to develop and offer applications via the Internet from a cloud service provider.Which cloud model is this user consuming?A. Software as a ServiceB. Platform as a ServiceC. Application as a ServiceD. Infrastructure as a ServiceAnswer: AExplanation:https://en.wikipedia.org/wiki/Cloud_computing#Service_modelsQUESTION 173Refer to the exhibit. Which three statements about this extract of the configuration of anautonomous AP are true? (Choose three) A. This configuration is of a non-root bridge access point.B. The RADIUS server IP address I misconfigured. It points to the AP itself. Which creates a loop for the RADIUS packets.C. This configuration allows bridging of VLANs 3 and 4.D. The SSID is not visible for clients proting the wireless medium.E. The administrator cannot access the AP via the web GUI using a secure connection.F. The native VLAN must be VLAN 1 to match the native VLAN configured on the switch to which the AP is connecting.Answer: CDEExplanation:Root bridge + basic Config of Autonomous AP + AP SSID boardcast -(=mbssid guest-mode) https://supportforums.cisco.com/document/61936/autonomous-ap-and-bridge-basic-configuration-template#Configurationon_Non_Root_bridgeLocal Radius

http://www.cisco.com/c/en/us/support/docs/wireless-mobility/wireless-lan-wlan/116580-configure-eapfast-00.htmlQUESTION 174Which option is a feature of a Cisco Autonormous AP that prevents over-the-air direct P2P communication, which forces all traffic to hit the first-hop router where security policy is enforced? A. Wi-Fi Direct Client Policy B. P2P Secure Packet C. Public Secure Packet ForwardingD. P2P Blocking Action Answer: CQUESTION 175Which statement about 802.11h is true?A. DFS feature works irrespective of whether the channel setting on WLC is set to auto or manual. B. 802.11h is not a mandatory standard under FCC regulations.C. The FCC does not require 802.11h to be supported in the 5 GHz band. D. When the radio detects a radar, it can use the channel for only 20 minutes at a time. Answer: AQUESTION 176In a converged access deployment, which two statements about mobility agents are true? (Choose two.)A. It maintains a client database of locally served clients.B. It manages mobility-related configuration.C. It handles RF functions.D. It is the first level in the converged access hierarchy.E. It is a mandatory element in the converged access design. Answer: ADQUESTION 177Heartbeats are used to maintain the high-availability status of an application. Which factor is most important? A. Bandwidth B. Latency C. Routing D. Round-trip time Answer: DOUESTION 178When a FlexConnect AP is in the "local authentication, local switching" state, it handles client authentication and switches client data packets locally. This state is valid in standalone mode and connected mode. Which three statements about a FlexConnect AP are true? (Choose three).A. In connected mode, the AP provides minimal information about the locally authenticated client to the controller. This information is not available on the controller policy type. Access VLAN. VLAN name, supported rates. Encryption ciphter.B. In connected mode, the access point provides minimal information about the locally authenticated client to the controller. However, this information is available to the controllerpolicy type., access VLAN, VLAN name, supported rates, encryption cipher.C. Local authentication is useful where you cannot maintain a remote office setup of a minimum bandwidth of 128 kbps with the round-trip latency no greater than 100 ms and the maximum transmission unit no smaller than 576 bytes.D. Local authentication is useful where you cannot maintain a remote office setup of a minimum bandwidth of 128 kbps with the round-trip latency no greater than 150 ms and the maximum transmission unit no higher than 500 bytes.E. Local authentication in connected mode does not require any WLAN configuration.F. Local authentication can be enabled only on the WLAN of a FlexConnect AP that is in local switching mode. Answer: ACFQUESTION 179On a Cisco 5760 WLC, which of the below is not part of the initial setup script?A. Wireless management interfaceB. Host nameC. HTTP server login accountD. SNMP Network ManagementE. NTP serverF. Enable passwordG. Default routing protocol Answer: GOUESTION 180You are setting up a Cisco access point in repeater mode with a non-Cisco access point as the parent and you use this interface configuration on your Cisco access point. You are getting the following error message. Which reason for this issue is true? A. "dot11 extension aironet" is missing under the interface Dot11Radio 0 interfaceB. When repeater mode is used, unicast-flooding must be enabled to allow Aironet IE communications.C. The parent AP MAC address has not been defined.D. Repeater mode only works between Cisco access points. Answer: CExplanation: parent mac address is missing without which bridging will not work. dot11 extensions aironet is an optional command without which the bridging should work.QUESTION 181A Cisco Unified 7925G Wireless IP Phone is operating on the 5 GHz band and transmitting at a power level of 40 mW. Which configuration must be done on the controller to

avoid one-way audio?A. In DCA, enable UNII-1 channels only.B. Set the maximum power level assignment to 26 dBm.C. In DCA, enable UNII-II channels only.D. Set the maximum power level assignment to 16 dBm.Answer: D!!!RECOMMEND!!!

1.|2019 Latest 400-351 Exam Dumps (PDF & VCE) 502Q&As Download:https://www.braindump2go.com/400-351.html2.|2019

Latest 400-351 Study Guide Video: YouTube Video: YouTube.com/watch?v=hZZnd7gWQik