

## [Jan-2019]100% Real Exam Questions-Braindump2go 400-151 Exam PDF and VCE 722Q Download(Q181-Q191)

**2019/January Braindump2go 400-151 Exam Dumps with PDF and VCE New Updated Today! Following are some new 400-151 Real Exam Questions:]1.[2019 Latest 400-151 Exam Dumps (PDF & VCE) 722Q&As**

**Download:**<https://www.braindump2go.com/400-151.html>**2.[2019 Latest 400-151 Exam Questions & Answers Download:**

<https://drive.google.com/drive/folders/0B75b5xYLjSSNOUtSMndmVjV3czA?usp=sharing>  
**QUESTION 181** Which three statements about the vTracker feature after it is enabled on the Cisco Nexus 1000v switch are true? (Choose three)  
A. The vTracker feature provides information about the virtual machines that are managed by all Cisco Nexus Switches.  
B. The vTracker feature uses the Link Layer Discovery Protocol.  
C. All vTracker views are valid for a given time only.  
D. The vTracker feature provides information about the virtual network environment.  
E. The VSM and vCenter must be on same subnet.  
F. The VSM must be connected with the vCenter to collect information.  
**Answer:** CDF  
**Explanation:**

[http://www.cisco.com/c/en/us/td/docs/switches/datacenter/nexus1000/sw/4\\_2\\_1\\_s\\_v\\_2\\_1\\_1/system\\_management/configuration\\_guide/b\\_Cisco\\_Nexus\\_1000V\\_System\\_Management\\_Configuration\\_Guide\\_2\\_1\\_1/b\\_Cisco\\_Nexus\\_1000V\\_System\\_Management\\_Configuration\\_Guide\\_2\\_1\\_1\\_chapter\\_010000.html](http://www.cisco.com/c/en/us/td/docs/switches/datacenter/nexus1000/sw/4_2_1_s_v_2_1_1/system_management/configuration_guide/b_Cisco_Nexus_1000V_System_Management_Configuration_Guide_2_1_1/b_Cisco_Nexus_1000V_System_Management_Configuration_Guide_2_1_1_chapter_010000.html) **QUESTION 182** Refer to the exhibit. Based on this portion of an MDS iSCSI configuration, which two statements are true? (Choose two)

A. The fc-lun 0x0000 mapping to iscsi-lun 0x0000 is not permitted.  
B. The iSCSI initiator that connects to target name iqn.1987-02.com.cisco.t3 will see two LUNs numbered as 2 and 4.  
C. The iSCSI initiator and the iSCSI target iqn.1987-02.com.cisco.t3 must be in the same zone before LUNs are available to the host.  
D. The iSCSI initiator at name iqn.1987-02.com.cisco.t2 has access to only one LUN.  
E. The iSCSI initiator that connects to target name iqn.1987-02.com.cisco.t3 will see two LUNs as numbers 0 and 1.  
**Answer:** CE  
**Explanation:**

**QUESTION 183** Refer to the exhibit, which two statements about spanning tree are true? (Choose two)  
A. BPDUs from a vPC are processed on this switch  
B. BPDUs are processed and generated by both peer switches.  
C. This switch cannot generate BPDUs for a vPC.  
D. BPDUs are sent to the peer switch for processing.  
E. BPDUs received on this switch are dropped because of Type 2 inconsistency issues.  
F. This switch generates BPDUs for vPC.  
**Answer:** CD

**QUESTION 184** In a high availability environment with two Fabric Interconnects, you can run a separate of Cisco UCS manager on each Fabric Interconnect. The Cisco UCS Manager on the primary Fabric Interconnect acts the primary management instance, and the Cisco UCS Manager on the other Fabric Interconnect is the subordinate management instance. Which of the following statements is true in regards to Fabric Interconnect management instance?  
A. The two instances of Cisco UCS Manager across a private network MGMT0 and MGMT1 Ethernet ports on the Fabric Interconnects.  
B. The two instances of Cisco UCS Manager across a private network L1 and L2 Ethernet ports on the Fabric Interconnects.  
C. The two instances of Cisco UCS Manager across a management network MGMT0 and MGMT1 Ethernet ports on the Fabric Interconnects.  
D. The two instances of Cisco UCS Manager across a management network L1 and L2 Ethernet ports on the Fabric Interconnects.  
**Answer:** B

**QUESTION 185** Refer to the exhibit. Which command would produce this output?  
A. show stats probe type  
B. show stats HTTPC  
C. show stats load balance  
D. show parameter map  
**Answer:** C

**QUESTION 186** Which command sends a test call Home Invertor message to start the registration process?  
A. test callhome inventory  
B. callhome inventory test  
C. test inventory callhome  
D. callhome test inventory  
**Answer:** D

**QUESTION 187** Drag and Drop Question  
Drag and drop sequence of the steps on left for ISSU software of dual supervisor switches to achieve a non-disruptive upgrade on the right.  
**Answer:**   
**QUESTION 188** Which two statements about basic zoning are true? (Choose two)  
A. If a zone is part of multiple zone sets you create one instance of this zone for both zone sets.  
B. To retrieve the results of the activation on a per switch basis. The managing switch provides a combined status about the activation and identifies the failure switch.  
C. Administrators can make simultaneous configuration changes. Upon activation one administrator can overwrite another administrator's changes.  
D. The default zone policy is defined per switch. To ensure smooth fabric operation, all switches in the fabric must have the same default zone setting.  
E. To distribute the zoning database, you must reactivate the same zone set. The reactivation may affect hardware changes for hard zoning only on the local switch, remote switch, remote switches are not affected.  
**Answer:** CD

**QUESTION 189** Which statement about soft pinning is incorrect?  
A. If no uplink Ethernet port channel is configured with all VLANs on the vNIC. Cisco UCS Manager drops the traffic for all of the VLANs on the vNIC.  
B. When the VLAN validation fails, a VLAN mismatch fault with a severity of warning appears.  
C. It is the default behavior Cisco UCS.  
D. Cisco UCS Manager pins the vNIC to an uplink Ethernet port or port channel according to VLAN membership criteria.  
**Answer:** B  
**Explanation:**

**QUESTION 190** Which two products provide the ability to create eight VDCs? (Choose two)  
A. Cisco Nexus 7000 Supervisor 2 Module  
B. Cisco Nexus 7000 Supervisor 1 Module  
C. Cisco Nexus 7700 Supervisor 1 Module  
D. Cisco Nexus 7700 Supervisor 2E Module  
E. Cisco Nexus 7000 Supervisor 2E Module  
**Answer:** DE  
**QUESTION 191** Refer to the exhibit, which two statements about the HSRPv6 implementation for company ABC are true? (Choose two)  
A. HSRP version #1 or #2 is supported.  
B. The UDP port is port 2029.

C.The virtual MAC address range is 0005.73A0.0FFF.D.The hop limit is set to 127.E.The multicast link-local IP destination address is FF08::66.Answer: **!!!RECOMMEND!!!**1.|2019 Latest 400-151 Exam Dumps (PDF & VCE) 722Q&As  
Download:<https://www.braindump2go.com/400-151.html>2.|**2019 Latest 400-151 Study Guide Video:** YouTube Video:  
[YouTube.com/watch?v=YgYCknRZclo](https://www.YouTube.com/watch?v=YgYCknRZclo)