[Jan-2019Exam Pass 100%!Braindump2go 400-151 VCE 722Q Instant Download(Q192-Q202)

2019/January Braindump2go 400-151 Exam Dumps with PDF and VCE New Updated Today! Following are some new 400-151 Real Exam Questions: 11, 2019 Latest 400-151 Exam Dumps (PDF & VCE) 722Q&As

Download:https://www.braindump2go.com/400-151.html2,|2019 Latest 400-151Exam Questions & Answers Download: https://drive.google.com/drive/folders/0B75b5xYLjSSNOUtSMndmVjV3czA?usp=sharingQUESTION 192Which mode must the Cisco MDS VSAN be configured for so that it interoperates correctly with a Brocade Fibre Channel switch that is configured for interop mode?A. interop mode 2B. interop mode 4C. interop mode 3D. native modeE. interop mode 1Answer: E QUESTION 193Refer to the exhibit. ABC company has successfully implemented the smart call home. Which three configuration components for CallHome are mandatory? (Choose three) A. periodic inventory intervalB. alert group to collect outputC. destination profileD. email server and from email addressE. contact informationF. system contactAnswer: DEFQUESTION 1940n Cisco Nexus 1000v Switch, you can allow the VSM and VEM to communicate over IP for control and packet traffic. Before you create a port profile for Layer 3 control, which two statements must be verified? (Choose two)A. Only one port profile can be configured with the capability Layer 3 control command.B. All VEMs belong to the same Layer 2 domain.C. The transport mode for the VSM domain should be configured as Layer 3.D. The port profile must be a trunk port profile.E. Different hosts should belong to the same VLANs for Layer 3 control. Answer: ACQUESTION 195Refer to the exhibit. Which two reasons explain why vPC peer-switch is not working? (Choose two) A. vPC peers are not the root of spanning tree topology.B. The peer keep alive link is down.C. Cisco Discovery Protocol is not configured.D. The feature is not enabled on the vPC peer.E. Loop Guard is disabled. Answer: BDQUESTION 196Which statement about NPV on the Cisco Nexus 5000 Series Switches is true? A. By default, Cisco Nexus 5000 Series Switches operate in NPV mode. In this mode, the switch provides standard Fibre Channel switching.B. In NPV mode, each switch that joins a SAN is assigned a domain ID. Each SAN (or VSAN) supports a maximum of 239 domain IDs, so the SAN has a limit of 239 switches.C. In NPV mode, the edge switch relays all traffic from server-side sports to the core switch. The core switch provides TE Port functionality to the downstream NPV switch.D. In NPV mode, the edge switch appears as a Fibre Channel host to the core switch and as a regular Fibre Channel switch to its connected devices. Answer: D OUESTION 197Drag and Drop QuestionDrag and drop the vPC feature on the left onto the correct description on the right. Answer: OUESTION 198Which description of how to enable DIMM blacklisting is true? A. Enable blacklisting in the servers > policy subtabB. Enable blacklisting in the servers inventory > memory subtabC. Configure a memory policy under the services tabD. Configure a memory policy in the equipment > policy subtabAnswer: AQUESTION 199Refer to the exhibit. An admin wants to bring online a new leaf node into their ACI fabric. Before registering the lead node, the admin checks the current status and sees this output. Which option is the reason for the admin to see this output? A. The DHCP server running on the APIC has failed and this the leaf node has not been able to obtain an IP addressB. The lead node is yet to be physically connected to the fabricC. This output is expected until the admin registers the leaf node and assigns it a roleD. This output is expected until the admin registers the lead node with an ID and nameE. This wrong catalog firmware is running on the APICAnswer: EQUESTION 200 Which two connectivity modes does Cisco RISE support? (Choose 2)A. Directly connected. No virtual port channel is supported. B. Indirectly connected. Only Layer 3 adjacent.C. Indirectly connected. Only Layer 2 adjacentD. Indirectly connected. Layer 2 and Layer 3 adjacent.E. Directly connected. Virtual port channel is supported. Answer: CEQUESTION 201Which three commands must be run to enable support of adapter-fex on an interface on Cisco Nexus Switch? (Choose 3)A. feature adapter-fex B. feature-set adapter-fexC. feature-set virtualizationD. feature fexE. switchport mode adapter-fexF. switchport mode vntag **Answer: ACFQUESTION** 202Which three distinct categories are within the cloud computing stack? (Choose 3)A. PaaSB. LaaS DaaSD. NaaSE. SaaSF. laaSAnswer: AEF!!!RECOMMEND!!!1.|2019 Latest 400-151 Exam Dumps (PDF & VCE) 722Q&As Download:https://www.braindump2go.com/400-151.html2.|2019 Latest 400-151 Study Guide Video: YouTube Video: YouTube.com/watch?v=YgYCknRZclo