

[March-2018-New100% Real Exam Questions-Braindump2go 352-001 Dumps PDF and VCE Dumps 510Q Download[139-149]

2018 March New Cisco 352-001 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 352-001 Real Exam Questions: 1.|2018 Latest 352-001 Exam Dumps (PDF & VCE) 510Q&As

Download:<https://www.braindump2go.com/352-001.html> 2.|2018 Latest 352-001 Exam Questions & Answers

Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNSUNBNi1aYkpfOTQ?usp=sharing> QUESTION 139Your company experienced a number of network incidents that had a significant impact on business operations. Because a root cause cannot be identified, your CTO asks you to help the network management team implement the FCAPS framework. On which two areas would you provide guidance to the network management team? (Choose two.)A. change managementB. accounting managementC. service level managementD. fault managementAnswer: BDQUESTION 140What are two benefits of using BFD for failure detection in the design of a network? (Choose two.)A. BFD can provide failure detection in less than one second.B. BFD can be used as a generic and consistent failure detection mechanism for EIGRP, IS-IS, and OSPF.C. BFD eliminates router protocol hello notification.D. BFD can be used for all types of network interfaces.E. BFD is independent of the network protocol.Answer: ABQUESTION 141You are designing a solution to eliminate the risk of high CPU utilization on a core network composed of CRS-1 devices. Which option would eliminate the risk of high CPU utilization across the network?A. Use Local Packet Transport Services (LPTS) to manage hardware SNMP flow rate.B. Use the in-band control plane policy feature to reduce the SNMP flow rate.C. Use the control plane policy feature and reduce SNMP flow rate.D. Use control-plane management-plane in-band and reduce the SNMP flow rate.E. Use the control-plane management-plane out-of-band feature to reduce the SNMP flow rate.Answer: AQUESTION 142In a network design using carrier Ethernet, which three mechanisms can be used to improve Layer 2 down detection and thereby reduce routing convergence time? (Choose three.)A. BFD.B. Ethernet port debounce timersC. link-state trackingD. object trackingE. fast IGP helloAnswer: ADEQUESTION 143The network administrator of a branch office network has decided to deploy Unicast RPF at the access layer. He insists that the design must guarantee that all the packets arriving on the router interfaces are assigned to the same interface subnet.Which mode of Unicast RPF would you recommend as the lead network designer?A. uRPF strict modeB. uRPF loose modeC. uRPF VRF modeD. RPF feasible modeAnswer: AQUESTION 144A senior network designer suggests that you should improve network convergence times by reducing BGP timers between your CE router and the PE router of the service provider. Which three factors should you to consider when you adjust the timer values? (Choose three.)A. access bandwidthB. service provider agreement to support tuned timersC. number of routes on the CE routerD. number of VRFs on the PE routerE. service provider scheduling of changes to the PEAnswer: ABCQUESTION 145Your design client has requested that you ensure that the client devices are not dynamically configured with incorrect DNS information. When finalizing the network design, which security option must be configured on the switches?A. IGMP snoopingB. DHCP snoopingC. root guardD. DNS snoopingAnswer: BQUESTION 146What are two functions of an NSSA in an OSPF network design? (Choose two.)A. It overcomes issues with suboptimal routing when there are multiple exit points from the area.B. It allows ASBRs to inject external routing information into the area.C. An ASBR advertises Type 7 LSAs into the area.D. An ABR advertises Type 7 LSAs into the area.E. It uses opaque LSAs.Answer: BCQUESTION 147As part of the security protocol for your network design, you have designated that option 82 is enabled for DHCP snooping. When option 82 is enabled, which information will be added to the DHCP request?A. switch MAC address and VLAN, module, and portB. remote ID and circuit IDC. switch IP address and VLAN, module, and portD. switch MAC address and switch IP addressAnswer: BQUESTION 148An IBGP mesh design is being scoped, and in the discussions, one of the design engineers proposes the use of route reflectors. Which limitation is valid when using route reflectors in thisdesign?A. The configuration complexity on the routers will be increased.B. Route reflectors will limit the total number of routes in the topology.C. Multipath information is difficult to propagate in a route reflector topology.D. Route reflectors will cause an opportunity to create routing loops.Answer: CQUESTION 149Your firm has been awarded a contract to design a Criminal Justice Information Services Version 5.0-compliant network utilizing advanced authentication policies. Which two methods could be utilized? (Choose two.)A. biometricB. PKIC. UKID. passwordAnswer: AB

!!!RECOMMEND!!!1.|2018 Latest 352-001 Exam Dumps (PDF & VCE) 510Q&As

Download:<https://www.braindump2go.com/352-001.html> 2.|2018 Latest 352-001 Study Guide Video: YouTube Video:

[YouTube.com/watch?v=CcH0sE7s21E](https://www.youtube.com/watch?v=CcH0sE7s21E)