

## [May-2018-NewValid Braindump2go 200-601 VCE and 200-601 PDF Dumps 90Q Offer[46-56]

2018 May New Cisco 200-601 Exam Dumps with PDF and VCE Just Updated Today! Following are some new 200-601 Real Exam Questions: 1.|2018 Latest 200-601 Exam Dumps (PDF & VCE) 90Q Download:

<https://www.braindump2go.com/200-601.html>2.|2018 Latest 200-601 Exam Questions & Answers Download:

<https://drive.google.com/drive/folders/0B75b5xYLjSSNWTIxdF9WZmZqMms?usp=sharing>QUESTION 46It is common to use Resilient Ethernet Protocol (REP) on the manufacturing floor as a resiliency protocol, as opposed to the Enterprise where it is not generally deployed. What are two reasons why REP is more suitable for the plant floor? (Choose two)A. REP is only supported on Industrial Ethernet switches, it is not supported on Catalyst switches.B. REP converges faster than Spanning Tree, allowing for greater network availability.C. REP supports Industrial Ethernet protocols better because it moves the packets faster.D. Running dual cables from access switches to an aggregation switch can have a much higher cost on the plant floor than in the Enterprise and running a ring protocol like REP provides resiliency at a lower cost.E. Industrial protocols can be negatively impacted by the number of nodes the Ethernet frame traverses, REP provides a topology with no more than 3 nodes for any data path.Answer: BDQUESTION 47Which scenario represents the correct configuration to support the SSIDs of this autonomous access point?A. MissingB. MissingC. MissingD. MissingAnswer: DQUESTION 48In which two ways could you minimize the impact of monitoring an industrial network? (Choose two.)A. Send random messages to a device and see what the response is.B. Do frequent ping sweeps to industrial devices to check for their proper operations.C. Make a copy of all the network traffic and analyze it offline.D. Use an industrial-network-grade IDS-IPS system.Answer: CDQUESTION 49Which option best describes the ProfiNET Discovery and Configuration Protocol (DCP)?A. Can be used to override both static and dynamically (DHCP/BOOTP) assigned IP addressesB. Cannot be used to reset a device to factory defaultsC. Is only supported in Conformance Class B and C devicesD. Uses the ProfiNET-IRT communication classAnswer: AQUESTION 50When troubleshooting a high packet loss condition in the network, the inspection area has an assessed M.I.C.E. value of M=1, I=1, C=3 and E=1. Which condition could be suspect?A. Use of shielded Patch Cables, Bonded on one end only.B. Use of unshielded Patch Cables.C. Broken seal on bulkhead connector.D. Oxidation on Shielded RJ45 Patch PlugAnswer: DQUESTION 51Refer to the exhibit. You are required to implement traffic segmentation in the network. See the table for relevant device details:

Device	Trunk	VLANs
L2SW4, L2SW5, and L2SW6	connected to L3SW1	with 802.1Q trunks with VLAN 191 and VLAN 398 allowed on the trunk.

You have the following information from L3SW1:

```
L3SW1# show run interfaces
interface Vlan1
no ip address
shutdown
!
interface Vlan2
ip address 10.2.2.2
255.255.255.248
!
interface Vlan191
ip address 10.10.27.126
255.255.255.192
!
interface Vlan200
ip address 10.20.20.1
255.255.255.248
!
interface Vlan398
ip address 10.15.153.1
255.255.255.0
L3SW1# show ip route
*** Output Omitted ***
10.0.0.0/8 is variably subnetted, 5 subnets, 3 masks
C 10.2.2.1/29 is directly connected, Vlan2
C 10.10.27.64/26 is directly connected, Vlan191
C 10.15.153.0/24 is directly connected, Vlan398
C 10.20.20.0/29 is directly connected, Vlan200
S* 10.200.200.0/24 [1/0] via 10.20.20.2
S* 0.0.0.0/0 [1/0] via 10.2.2.1
```

You are required to implement a configuration that will meet the following connectivity requirements:

- The Administrator's Station must have full access to PanelView-
- PanelView should have limited access, based on specific TCP ports, to PLC#1 and I/O#1-
- The Administrator's Station should have no access to PLC#1 and I/O#1-
- PLC#1 and I/O#1 should be able to communicate with each other on any port

Which action will allow you to meet the connectivity requirements?A. Put interface VLAN 191 and interface VLAN 398 into different Virtual Routing and Forwarding (VRF) instances on L3SW1B. Deploy an inbound ACL on interface VLAN 191 to control the traffic from the Administrator's Station and PanelView to PLC#1 and I/O#1C. No change is required, the traffic is already limited appropriately by the VLAN segmentationD. Implement an ACL on Firewall1 to control the traffic flow between VLAN 191 and VLANAnswer: BQUESTION 52It is determined that an intermittent high packet loss event is occurring within a segment of the network. The assigned task is to determine the cause. Which of these conditions should be suspected?A. MissingB. MissingC. MissingD. MissingAnswer: DQUESTION 53You have been tasked to design an Ethernet network capable of Motion control with cycle times not to exceed 1ms. In order to create a more deterministic network, what characteristic/s should you primarily focus on?A. Latency and JitterB. Redundancy and high availabilityC. Explicit and Implicit messagingD. This cycle time is not possible on an Ethernet networkE. Gigabit port speedAnswer: AQUESTION 54ProfiNET has been disabled on a Cisco Industrial Ethernet switch. Which CLI command will correctly enable ProfiNET on the switch?A. switch(config)#profinetB. switch(config-if)#switchport profinet vlan 10C. switch(config)#vlan 10 profinetD. switch#enable profinetAnswer: AQUESTION 55Which describes a best practice rule for controlling traffic between the corporate network and the controls network?A. Outbound traffic from the control network to the corporate network and outbound traffic from the corporate network to the control network can be restricted based on source and destination address only.B.

Outbound traffic from the corporate network to the control network should be restricted but outbound traffic from the control network to the corporate network should not be restricted.C. Outbound traffic from the control network to the corporate network should be restricted based on source and destination address and service only.D. Outbound traffic from the control network to the corporate network should be restricted based on source and destination address, service, and port.  
Answer: D  
QUESTION 56  
Which statement is true regarding ProfiSAFE?  
A. ProfiSAFE traffic must be carried on a network that is physically separated from automation traffic  
B. ProfiSAFE relies on the error detection mechanisms of Ethernet and TCP/IP to determine if there are network errors  
C. ProfiSAFE can be used in safety applications up to Safety Integrity Level 3 (SIL3)  
D. ProfiSAFE is only used by ProfiBUS PA and ProfiBUS DA devices  
Answer: C  
**!!!RECOMMEND!!!**  
1. |2018 Latest 200-601 Exam Dumps (PDF & VCE) 90Q  
Download: <https://www.braindump2go.com/200-601.html>  
2. |2018 Latest 200-601 Study Guide Video: YouTube Video:  
[YouTube.com/watch?v=07100ZztBOA](https://www.youtube.com/watch?v=07100ZztBOA)