[May-2019-NewValid Braindump2go 100-105 VCE and PDF 729Q Offer

2019/May Braindump2go 100-105 Exam Dumps with PDF and VCE New Updated Today! Following are some new 100-105 Real Exam Questions: 1. 2019 Latest 100-105 Exam Dumps (PD & VCE) Instant

Download:https://www.braindump2go.com/100-105.html2.|2019 Latest 100-105 Exam Questions & Answers Instant Download:https://drive.google.com/drive/folders/0B75b5xYLjSSNZW1Fd3pCZzBVLWs?usp=sharingNew QuestionWhich set of conditions comprises a successful ping attempt between two connected routers configured with IP addresses on the same subnet?A. The destination host receives an echo reply from the source host within one second and the source host receives an echo request from the destination host.B. The destination host receives an echo request from the source host within one second.C. The destination host receives an echo reply from the source host within one second and the source host receives an echo reply from the destination host within two seconds.D. The destination host receives an echo request from the source host and the source host receives an echo request from the destination host within one second.E. The destination host receives an echo request from the source host and the source host receives an echo reply from the destination host within two seconds. Answer: ENew QuestionWhat happens when the cable is too long?A. Baby GiantB. Late collisionAnswer: BNew QuestionWhich two VLANs are reserved for system use only? (Choose two)A. 1B. 4095C. 4096D. 0E. 1001Answer: BDExplanation: The VLANs 0 and 4095 are reserved by the IEEE 802.1Q standard and you cannot create, delete, or modify them so they are the correct answers.Note:+ VLAN 0 and 4095 are reserved for system use only. You cannot see or use these VLANs.+ VLAN 1 and VLANs 1002-1005 are default VLANs. Default VLANs are created automatically and cannot be configured or deleted by users. + VLAN 2 to 1001 are normal VLANs. You can create, use and delete them. + VLAN 1002 to 1005 are normal VLANs too but Cisco reserved for FDDI an Token Ring.New QuestionWhat is the requirement of configuring 6to4 tunnelling on two routers?A. Both ipv6 and ipv4 must be configuredB. Only IPv6C. Only IPv4Answer: ANew QuestionWhich name describes an IPV6 host-enable tunneling technique that uses IPV4 UDP, does not require dedicated gateway tunnels, and can pass through existing IPV4 NAT gateways?A. dual stack XXB. dynamicC. TeredoD. Manual 6to4Answer: CNew QuestionWhich sequence begins a unique local IPv6 address in binary notation?A. 00000000B. 1111110C. 1111100D. 1111111Answer: BNew QuestionWhich statement about 6to4 tunneling is true?A. One tunnel endpoint must be configured with IPv4 onlyB. It establishes a point-to-point tunnelC. Both tunnel endpoints must be configured with IPv4 onlyD. Both tunnel endpoints must support IPv4 and IPv6Answer: DNew QuestionWhat is true about ipv6 unique local addresses: A. Global idB. Public routableC. SummarizationD. Unique prefix Answer: DNew QuestionHow do you bypass password on cisco device?A. Change the configuration register to 0x2142. With this setting when that router reboots, it bypasses the startup-config and no password is required. Answer: ANew Question How many primary ipv4 addresses can be assigned on router interface ?A. 0B. 1C. 4D. UnlimitedAnswer: DNew Question Which command is used to build DHCP pool?A. ipdhcp conflictB. ipdhcp-server pool DHCPC. ipdhcp pool DHCPD. ipdhcp-client pool DHCPAnswer: C!!!RECOMMEND!!!1./2019 Latest 100-105 Exam Dumps (PD & VCE) Instant Download:https://www.braindump2go.com/100-105.html2.|2019 Latest 100-105 Study Guide Video Instant Download: YouTube Video: YouTube.com/watch?v=rVAmvvPeRhU