

## [New-400-151-Dumps] 400-151 Exam PDF and VCE Dumps 122q Exam Files Free Download from Braindump2go[41-50]

2016/12 New Cisco 400-151: CCIE Data Center Written Exam v2.0 Exam Questions Updated Today! Free Instant Download  
400-151 Exam Dumps (PDF & VCE) 122Q&As from Braindump2go.com Today! 100% Real Exam Questions! 100% Exam Pass Guaranteed!  
1. | 2016/12 New 400-151 Exam Dumps (PDF & VCE) 122Q&As Download:  
<http://www.braindump2go.com/400-151.html> 2. | 2016/12 New 400-151 Exam Questions & Answers:  
<https://1drv.ms/f/s!AvI7wzKf6QBjgTGwhbcWvLDn5gQS> QUESTION 41 Refer to the exhibit. Which option describes when this server reboots? A. When the vnic/vhba placement is changed B. When the user acknowledges the reboot C. Immediately after the next change D. When the schedule is set to occur. Answer: A QUESTION 42 You want to make 80 Gbps of bandwidth available to your Redhat Servers. Which two statements are true? (Choose 2) A. Install 2204 IOMs, VIC1240 CNAs, fabric Extenders, and create four vNICs mapped to each fabric. B. Install 2208 IOMs, VIC1280 CNAs, fabric Extenders, and create four vNICs mapped to each fabric. C. Install 2208 IOMs, VIC1280 CNAs, fabric Extenders, and create eight vNICs mapped to each fabric. D. Install 2204 IOMs, VIC1280 CNAs, fabric Extenders, and create four vNICs mapped to each fabric. E. Install 2204 IOMs, VIC1280 CNAs, and create four vNICs mapped to each fabric. F. Install 2204 IOMs, VIC1240 CNAs, and create four vNICs mapped to each fabric. Answer: CF QUESTION 43 Refer to the exhibit. Which two options are possible reasons for device being stuck in "init" mode? (Choose 2) A. Incorrect VM is selected B. Incorrect "Function type" is selected. C. No "Chassis" is selected. D. "Http service enable" is not configured on the ASAE. Incorrect credentials are provided. F. No management interface is specified in "cluster interfaces" section Answer: DE QUESTION 44 Refer to the exhibit. After you upgrade Cisco UCS firmware, some of your blades have these error messages. Which description of the problem is true? A. Storage provisioning is not configured B. vNIC template must be converted to updating. C. Some components are deprecated. D. Service profile requires a connectivity policy. Answer: D QUESTION 45 After VTEP devices are established BGP neighbor adjacencies with other VTEPs or with internal BGP route reflector, which three pieces of information are exchanged through BGP? (Choose 3) A. Layer 3 VNIB. VPNv4 prefixes C. Router MAC address D. VTEP peer list E. VTEP address Answer: ACE QUESTION 46 Which three statements about IP source guard are true? (Choose 3) A. IP source Guard is dependent upon DHCP snooping to build and maintain the IP-MAC-Address binding table or upon manual maintenance of static IP-source entries. B. IP source guard requires that CHCP snooping is disabled. C. By default, IP source guard is enabled on all interfaces. D. IP source guard limits IP traffic on an interface to only those sources that have an IP=MAC address binding table entry or static IP source entry. E. When you first enable IP source guard on an interface, you may experience disruption in IP traffic until the hosts on the interface receive a new IP address from a DHCP server. Answer: ADE QUESTION 47 Which three PVLAN port models are supported on Cisco necus 9000? (Choose 3) A. Isolated host B. FEX port C. Port Channels D. Isolated host trunk E. Virtual port channels F. Community host Answer: ADF QUESTION 48 Which two statements about policing, queuing, and scheduling are true? (Choose 2) A. You can schedule traffic by imposing a maximum data rate on a class of traffic so that excess packets are dropped. B. Policing is the monitoring of data rates for a particular class of traffic. The device can also monitor associated burst sizes. C. You can apply weighted random early detection to a class of traffic, which allows packets to be dropped to be dropped based on the CoS field. D. The WRED algorithm is reactive approach only to traffic congestion. Answer: BC QUESTION 49 Which three main functions are provided by OTC to achieve failure isolation? (Choose 3) A. ARP optimization B. Use of multiple ORC overlays C. Unknown unicast traffic suppression D. Spanning tree isolation E. Optimal outbound routing Answer: ACD QUESTION 50 Refer to the exhibit. Within an ACI fabric, routing protocol is needed to assist with router redistribution between the outside networks and the internal fabric. Which routing protocol is needed to run in the fabric at location 1 to allow the VM access to the networks advertised by the external layer 3 network? A. MP-BGP B. EBGPC. iBGP D. OSPFE. IS-IS Answer: A !!!RECOMMEND!!!  
1. Braindump2go | 2016/12 New 400-151 Exam Dumps (PDF & VCE) 122Q&As Download:  
<http://www.braindump2go.com/400-151.html> 2. Braindump2go | 2016/12 New 400-151 Study Guide: YouTube Video:  
[YouTube.com/watch?v=17-eCNdml4Y](https://www.youtube.com/watch?v=17-eCNdml4Y)