## [New Exams!Free Download Braindump2go 300-365 Exam VCE and PDF Dumps[21-30

2017 Sep New Braindump2go 300-365 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 300-365 Questions: 1.|2017 New 300-365 Exam Dumps (PDF & VCE) 70Q&As Download:https://www.braindump2go.com/300-365.html 2.|2017 New 300-365 Exam Questions & Answers Download:

https://drive.google.com/drive/folders/0B75b5xYLjSSNZTJ3Y0Z5b0NFRFE?usp=sharing QUESTION 21You have just added a new MSE to Prime Infrastructure and want to synchronize the MSE with your 5508 WLC. which is located behind a firewall in a DMZ. You notice that NMSP messages are failing between the two devices. What traffic needs to be allowed on the Firewall to ensure the MSE and WLC can communicate using NMSP? A. UDP 16113B. TCP 1613C. TCP 16113D. UDP 1613 Answer: C QUESTION 22When a Vocera badge performs a broadcast call in a properly configured VoWLAN using WLC v7.0, which two choices indicate how the QoS is marked? (Choose two.) A. Upstream marked as Best Effort.B. Upstream marked as ToS CS4.C. Upstream amarked as DSCP EF.D. Downstream marked as DSCP EF.E. Downstream marked as Best Effort.F. Downstream marked as Silver. Answer: CE QUESTION 23A network engineer is debugging issues with the mDNS gateway. Which type of reply should be seen in the Wireshark capture when querying for a mDNS service in the Bonjour Cache? A. unicast from Prime InfrastructureB. unicast from controllerC. multicast from devicesD. multicast from controllerE. unicast from devicesF. multicast from Prime Infrastructure Answer: B QUESTION 24An engineer would like to capture NetFlowdata on PI. Which resource is required to allow this? A. Cisco MSE as NetFlow exporterB. Prime Infrastructure 1.0 or laterC. Cisco NAC as NetFlow exporterD. Cisco ISE as NetFlow exporter Answer: B QUESTION 25Which statement about when you configure FlexConnect APs and you want to set up Cisco Centralized Key Management fast roaming is true? A. FlexConnect groups are required for Cisco Centralized Key Management fast roaming to work with FlexConnect access points.B. APs that are in the same FlexConnect group but associated to different WLCs support Cisco Centralized Key Management.C. Cisco Centralized Key Management fast roaming among FlexConnect and non-FlexConnect access points is supported.D. The FlexConnect access point (WLC) >show interface su must be in standalone mode to support Cisco Centralized Key Management. Answer: A QUESTION 26Refer to Exhibit. Interface Name

A wireless client is connecting to FlexAPI which is currently working standalone mode. The AAA authentication process is returning the following AVPs:Tunnel-Private-Group-ld(81): 15 Tunnel-Medium-Type(65):IEEE-802(6) Tunnel-Type(64): VLAN(13)Which three behaviors will the client experience? (Choose three.) A. While the AP is in standalone mode, the client will be placed in VLAN 15.B. While the AP is in standalone mode, the client will be placed in VLAN 10.C. When the AP

transitions to connected mode, the client will be de-authenticated.D. While the AP is in standalone mode, the client will be placed in VLAN 13.E. When the AP is in connected mode, the client will be placed in VLAN 13.F. When the AP transitions to connected mode the client will remain associated.G. When the AP is in connected mode, the client will be placed in VLAN 15.H. When the AP is in connected mode, the client will be placed in VLAN 10. Answer: ADE QUESTION 27The customer has deployed C7960 phones with clients connected to them. What switch feature could be enabled to distinguish IP voice traffic from client data traffic? A. VoiceVLANB. QoS routingC. WMED. Weighted QueuingE. QBSS Answer: A QUESTION 28An engineer wants to configure Call Admission Control and ensure that AC is based on the capacity of the AP and considering the possible impact of other APs in the area. Which two configuration options are required? (Choose two.) A. StaticCACB. Admission ControlC. Load-Based ACD. Add Traffic StreamE. Reserved Roaming BandwidthF. Expedited Bandwidth Answer: BC QUESTION 29A FlexConnect remote office deployment is using five 2702i APs indoors and two 1532i APs outdoors. When a code upgrade is performed and FlexConnect Smart AP Image Upgrade is leveraged, but no FlexConnect Master AP has been configured. How many image transfers between the WLC and APs will occur? A. 7B. 1C. 5D. 2 Answer: D QUESTION 30What is the default NMSP echo interval between a Mobility Services Engine and Wireless LAN Controller? A. 30SecondsB. 15 SecondsC. 10 SecondsD. 60 Seconds Answer: B !!!RECOMMEND!!! 1.|2017 New 300-365 Exam Dumps (PDF & VCE) 70Q&As Download:https://www.braindump2go.com/300-365.html 2.|2017 New 300-365 Study Guide Video: YouTube Video: YouTube.com/watch?v=h9iX dHUEPs