

[September-2022]Free Braindump2go New JN0-104 Dumps JN0-104 320Q[Q287-Q302]

September/2022 Latest Braindump2go JN0-104 Exam Dumps with PDF and VCE Free Updated Today! Following are some new Braindump2go JN0-104 Real Exam Questions!
QUESTION 287You enable unicast reverse path forwarding on the ge-0/0/1.0 interface. A packet is received on the ge-0/0/1.0 interface with a source address of 10.10.10.10. A route lookup determines that the next hop for the 10.10.10.10 address is the ge-0/0/1.0 interface. In this scenario which action is performed?
A. The packet is logged
B. The packet is forwarded
C. The packet is rejected
D. The packet is discarded
Answer: B
Explanation:
<https://www.juniper.net/documentation/us/en/software/junos/security-services/topics/topic-map/interfaces-configuring-unicast-rpf.html>
QUESTION 288Referring to the exhibit, what happens when you issue the exit command at the [edit protocols ospf area 0.0.0.51 stub hierarchy level?

```
(edit protocols ospf)
user@router# edit area 51 stub
(edit protocols ospf area 0.0.0.51 stub)
user@router# exit
```

A. You move one level up to the [edit protocols ospf area 0.0.0.51] hierarchy level.
B. You exit the configuration mode.
C. You move to the [edit] hierarchy level.
D. You move to the most recent higher level of the [edit protocols ospf] hierarchy.
Answer: D
QUESTION 289Assuming both paths shown in the exhibit are available, which statement is correct?

```
(edit routing-options)
user@router# show
static {
    route 0.0.0.0 {
        next-hop 172.16.1.1
        qualified-next-hop 172.16.1.254
        preference 4
    }
}
```

A. Traffic matching the default route will use 172.16.1.1 as the next hop.
B. Traffic matching the default route will use 172.16.1.254 as the next hop.
C. Traffic matching the default route will be load-balanced per flow across both next hops.
D. Traffic matching the default route will be load-balanced per packet across both next hops.
Answer: B
QUESTION 290Which attribute must be defined when configuring a non-root user in Junos OS?
A. class
B. uid
C. authentication
D. full-name
Answer: A
Explanation: UID is optional (it is automatically set) whereas class is required:

<https://www.juniper.net/documentation/us/en/software/junos/user-access/topics/topic-map/junos-os-user-accounts.html>
QUESTION 291In the show | compare rollback 49 command, what is the purpose of the | ?
A. The | is used to represent an "either or" statement
B. The | is a shortcut to redirect output from a command line to a file
C. The | filters the output of the show command
D. The | changes the command from an operational command to a configuration mode command
Answer: C
QUESTION 292What are two benefits of a modular operating system? (Choose two.)
A. Each module runs in its own protected memory space
B. It enables the independent restart of each module as necessary
C. A malfunction in one module causes a full system shutdown
D. It enables CPU scheduling strictly using kernel system calls
Answer: AB
QUESTION 293Referring to the exhibit, you are unable to see any traffic coming on interface ge-0/0/0. What is causing this problem?

```
user@router> show interfaces ge-0/0/0 extensive
Physical interface: ge-0/0/0, Enabled, Physical link is Down
Interface index: 137, SNMP ifindex: 508, Generation: 140
Link-level type: Ethernet, MTU: 1514, LAN-PHY mode, Link-mode: Full-duplex,
Speed: 10Gbps, BPDU Error: None, Loop Detect PDU Error: None,
Ethernet-Switching Error: None, MAC-REWRITE Error: None, Loopback: Disabled,
Source filtering: Disabled, Flow control: Enabled
Device flags: 0x00000000, Running
Link flags: 0x00000000, None
CoS queues: 8 supported, 8 maximum usable queues
Hold-times: Up 0 ms, Down 0 ms
Current address: 00:50:56:a9:03:76, Hardware address: 00:50:56:a9:03:76
Last flapped: 2021-04-06 04:56:12 PDT (1d 07:12 ago)
Statistics last cleared: Never
Traffic statistics:
```

A. The ge-0/0/0 interface is administratively down
B. The ge-0/0/0 interface has flow control disabled
C. The ge-0/0/0 interface's physical link is down
D. The ge-0/0/0 interface has the link-mode set to half-duplex
Answer: C
QUESTION 294 Which command should you use to check real-time statistics of all active interfaces?
A. user@router> monitor interface traffic
B. user@router> show interface detail
C. user@router> show interface terse
D. user@router> monitor traffic extensive
Answer: A
QUESTION 295 What happens when you filter the output of a command using the no-more parameter?
user@router> show interfaces | no-more
A. The output is displayed in XML format
B. The output is displayed with no page breaks
C. The last screen of information is displayed
D. The number of lines in the output are displayed
Answer: B
QUESTION 296 You loaded the factory-default configuration on your Junos device. Which single element must be configured before a commit command will succeed?
A. An IPv4 address must be configured on the fxp0 or em0 interface
B. A hostname must be configured
C. A root password must be configured
D. An IPv4 default route must be configured
Answer: C
QUESTION 297 Which two statements describe the functions of the Routing Engine (RE)? (Choose two.)
A. The RE will apply filters and routing policies when forwarding the packets to their final destination
B. The RE will route or switch packets or frames out of the correct interface as quickly as possible
C. The RE will calculate the best network path to each individual subnet based on input from various routing protocols and static routes
D. The RE will process management traffic to help monitor and manage the network device
Answer: CD
QUESTION 298 Which two statements about the output shown in the exhibit are correct? (Choose two.)

```
user@router> show ospf neighbors
Address      Interface  Pri  Dead
172.25.1.1   ge-0/0/2.0  Full  192.168.100.2  128  35
```

A. The router ID of the neighbor connected to the ge-0/0/1.0 interface is 192.168.100.3
B. The router has two OSPF adjacencies
C. The neighbors are not using the Junos OS default OSPF priority value
D. The IP address assigned to the router's ge-0/0/1.0 interface is 172.25.1.9
Answer: AB
QUESTION 299 Referring to the exhibit, which two statements are correct? (Choose two.)

```
user@router> show
Routing Engine at
Total Memory
Control plane
Data plane
5 sec CPU utilization
User
Background
Interrupt
Idle
Model
Start time
Uptime
Last reboot
Load average
```

A. The last 5 second CPU utilization is 1%
B. The last 5 second CPU utilization is 99%
C. The control plane memory used is 63%
D. The data plane memory used is 63%
Answer: AD
QUESTION 300 Which two operating systems are used as the foundation of the Junos OS? (Choose two.)
A. Linux
B. Ubuntu
C. CentOS
D. FreeBSD
Answer: AD
QUESTION 301 Which two statements about firewall filters are correct? (Choose two.)
A. An input filter is used to control routes that are accepted by the local routing table
B. An output filter determines the routes in the local routing table that are advertised to peers
C. An input filter is used to control incoming traffic on a specific interface
D. An output filter is used to control outgoing traffic on a specific interface
Answer: CD
QUESTION 302 [edit]user@router# In which mode is the system currently operating, as shown in the exhibit?
A. operational mode
B. UNIX shell
C. configuration mode
D. single-user mode
Answer: C

Resources From: 1.2022 Latest Braindump2go JN0-104 Exam Dumps (PDF & VCE) Free Share: <https://www.braindump2go.com/jn0-104.html> 2.2022 Latest Braindump2go JN0-104 PDF and JN0-104 VCE Dumps Free Share:

<https://drive.google.com/drive/folders/1wBXsGfOqI-eYIzP06rVVSLSkvIHuDhg9?usp=sharing> 3.2021 Free Braindump2go JN0-104 Exam Questions Download:

<https://drive.google.com/drive/folders/1wBXsGfOqI-eYIzP06rVVSLSkvIHuDhg9?usp=sharing> Free Resources from Braindump2go, We Devoted to Helping You 100% Pass All Exams!