[Updated 300-101 DumpsValid Braindump2go 300-101 Brain Dumps PDF 739Q Offer[Q666-Q676

2018/10/22 Braindump2go 300-101 Exam Dumps with PDF and VCE New Updated Today! Following are some new 300-101 Real Exam Questions: 1.|2018 Latest 300-101 Exam Dumps (PDF & VCE) 739Q&As

Download:https://www.braindump2go.com/300-101.html2.|2018 Latest 300-101 Exam Questions & Answers Download:https://drive.google.com/drive/folders/0B75b5xYLjSSNUlpIeEc2YV9vRDg?usp=sharingQUESTION 666Which two statements about NAT in a DMVPN environment are true?(Choose two)A. a hub router can be behind a dynamic NAT on a device.B. Spoke routers can reside only on the public side of a NAT device.C. Two spokes can establish session among themselves using PAT behind different NAT devices.D. A spkoke router can be represented by a static NAT on a device.E. A hub router can user static NAT for its buplich UP address. Answer: DEQUESTION 667Which adverse circumstance can the TTL feature prevent?A. routing loopsB. DoS attacksC. link saturationD. CAM table overloadAnswer: AQUESTION 668Which two features are provided by EIGRP for IPv6? (choose two)A. Backbone areasB. SPF algorithmC. Partial updatesD. Area border routerE. Scaling Answer: CEQUESTION 669Which two EIGRP metrics have nonzero K values by default? (Choose two.)A. reliabilityB. delayC. costD. loadE. bandwidthAnswer: BEQUESTION 670Whcih two features does RADIUS combine? (Choose two)A. authorizationB. authenticationC. sshD. accountingE. TelnetAnswer: ABQUESTION 671Refer to the exhibit. You want router r1 to perform unequal-cost routing to the 172.168.10.0/24 network. What is the smallest EIGRP variance value that you can configure on R1 to achieve this result? A. 1B. 2C. 3D. 4Answer: CQUESTION 672Which IP SLA operation can be used to simulate voice traffic on a network?A. TCP connectB. UDP-jitterC. ICMP-echoD. ICMP-jitter Answer: BQUESTION 673Device R1 has 1 Gigabit and 10 Gigabit Ethernet interfaces, Which command do you enter so that takes full advantage of OSPF costs? A. R1(config router)#auto-cost reference-bandwidth 10000B. R1(config route-map)#set metric 1000000000C. R1(config if)#ip ospf cost 10000D. R1(config router)#auto*cost reference-bandwidth 1000000000E. R1(config if)# ip ospf cost 100000000F. R1(config route-map)#set metric 10000Answer: AQUESTION 674In which network environment is AAA with RADIUS most appropriate?A. when Apple Talk Remote Access is in userB. when NetBIOS Frame Control Protocol is in useC. when users require access to only one device at a timeD. when you need to separate all AAA services Answer: COUESTION 675 Which command sequence can you enter on a router configure Unicast Reverse Path Forwarding in loose mode?A. Interface GigabitEthernet0/0ip verify unicast source reachable-via looseB. Interface GigabitEthernet0/0ip verify unicast source reachable-via allC. Interface GigabitEthernet0/0ip verify unicast source reachable-via anyD. Interface GigabitEthernet0/0ip verify unicast source reachable-via rxAnswer: CQUESTION 676Which SNMP model and level can provide DES encryption? A. SNMPV2 noAuthNoPrryB. SNMPV3 authNoPrivC. SNMPV3 authEnD. SNMPV3 noAuthNoPrvAnswer: C!!!RECOMMEND!!!1.|2018 Latest 300-101 Exam Dumps (PDF & VCE) 739Q&As Download:https://www.braindump2go.com/300-101.html2.|2018 Latest 300-101 Study Guide Video: YouTube Video: YouTube.com/watch?v=6lHfKlW8bNY